

COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

API NO. 30-025-01858

6. Indicate Type of Lease
State ☒ Free ☐

5. State Oil & Gas Lease No.

E-906

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. SEE APPLICATION FOR PERMIT - "A" (FORM C-101) FOR SUCH PROPOSALS.)

7. Unit Agreement Name

8. Farm or Lease Name

Ranger

9. Well No.

10

10. Field and Pool, or Wildcat

Ranger Lake Penn

12. County	Lea
------------	-----

OIL WELL ☐ GAS WELL ☐ OTHER ☐

11. Name of Operator

Phillips Petroleum Company

Address of Operator

Room 401, 4001 Penbrook St., Odessa, Texas 79762

Location of Well

UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM

THE West LINE, SECTION 26 TOWNSHIP T-12-S RANGE R-34-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

4161' DF 4162' RKB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

OTHER ☐

NOTE: DCH-193 includes Ranger Lake Bough
Total well bore P&A

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-30-79 Pulled tbq, pump and equipment. Ran 2-3/8" tbq to 10,310'. Spotted 65 sxs of Class "H" cmt, 1/4 bbls of Flocele in first 25 sxs. Displaced cmt out of tbq w/37 bbls mud, raised tbq 9500', reversed clean w/45 bbls mud. Tagged top of cmt at 10,220'. Spotted w/65 sxs Class "H" cmt, displaced w/37 bbls mud, raised tbq to 9500', reversed clean w/45 bbls mud.

10-31-79 Tagged TOC at 9752'. Spotted cmt plug at 5566', 50 sxs plug at 2179-1760'. Pulled tbq to 1714'. Circ hole clean. Perfd 4 shots at 250'. Circ 100 sxs cmt to surface. Cut off wellhead, weld on plate, and install permanent marker. P&A.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *W. J. Mueller* W. J. Mueller

TITLE Senior Engineering Spec.

DATE 11-12-79

OIL & GAS INSPECTOR

JUL 24 1980

APPROVED BY *W. J. Mueller*

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: