

NEW MEXICO OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

WELL RECORD

1961 MAY 23 11 52 AM
MAN TO DISTRICT OFFICE OIL CONSERVATION COMMISSION, TO WHICH FORM
CARD WAS SENT NOT LATER THAN TWENTY DAYS AFTER COMPLETION OF WELL.
FOLLOW INSTRUCTIONS IN RULES AND REGULATIONS OF THE COMMISSION.
SUBMIT IN QUINTUPPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

HUMBLE OIL & REFINING COMPANY
(COMPANY OR OPERATOR)

WELL NO. 1, IN SE 1/4 OF NW 1/4 OF SEC. 23, T. 13-S, R. 34-E, NMPM.
Pennsylvanian POOL, Los. COUNTY.

WELL IS 1900 FEET FROM North LINE AND 1980 FEET FROM West LINE
OF SECTION 23. STATE LAND THE OIL AND GAS LEASE NO. 8.

DRILLING COMMENCED August 9, 1961. DRILLING WAS COMPLETED September 25, 1961.

NAME OF DRILLING CONTRACTOR John Drilling Company
ADDRESS Odessa, Texas

ELEVATION ABOVE SEA LEVEL AT TOP OF TIER'S HEAD 4143 D.F. THE INFORMATION GIVEN IS TO BE
KEPT CONFIDENTIAL UNTIL 12. Date Well P&A: 10-10-61

OIL SANDS OR ZONES

NO. 1, FROM Dry Hole TO NO. 4, FROM TO
NO. 2, FROM TO NO. 5, FROM TO
NO. 3, FROM TO NO. 6, FROM TO

IMPORTANT WATER SANDS

INCLUDE DATA ON RATE OF WATER INFLUX AND ELEVATION TO WHICH WATER CAME IN WELL.

NO. 1, FROM TO FEET
NO. 2, FROM TO FEET
NO. 3, FROM TO FEET
NO. 4, FROM TO FEET

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	DEPTH	END OF PIPE	CUT VAL PULLED OUT	PERFORATIONS	PURPOSE
9"	47	New	365	Larkin	None	"	Surface
3-5/8"	24	New	4337	Baker	1355	"	Oil string

MUDLOG AND CEMENTING REPORT

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	MUD USED	MUD GRAVITY	AMOUNT OF MUD USED
15	9"	379	375	Pumped		
10-5/8	8-5/8"	4250	60	Pumped		
See below for plugs:						

RECORD OF PRODUCTION AND STIMULATION

(RECORD THE PRODUCTION NO. OF OIL OR GAS, USED, EITHER TREATED OR NOT)

Plug #1 set from 10,600 to 10,200 w/130 sacks, Plug #2 set from 9550 to 9290 with 20

sacks, Plug #2 set from 7100 to 6000 with 20 sacks, Plug #3 set from 5100 to 4800 with

90 sacks, Plug #2 set from 4800 to 4200 with 35 sacks, Plug #6 set from 3590 to 3150

with 110 sacks, Plug #7 set from 1390 to 1325 with 40 sacks, Plug #8 set from 1400 to
330 with 50 sacks and Plug #9 set from 20 to surface with 15 sacks.