

**TRIPPLICATE**

**NEW MEXICO OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico

**MISCELLANEOUS NOTICES**

Submit this notice in TRIPPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

**Hobbs, New Mexico**  
(Place)

**November 17, 1956**  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the West Tatum Unit

Skelly Oil Company Well No. 1 in WVW  
(Company or Operator) (Unit)  
SE 1/4 SW 1/4 of Sec. 26, T. 12S, R. 35E, NMPM., Wildcat Pool  
(40-acre Subdivision) Lee County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Drilled to T.D. 13,563', 13-3/8" OD casing set at 314' and cemented to surface, 9-5/8" OD casing set at 4,211' and cemented to surface. No oil or gas in commercial quantities was encountered in any zone. We propose to plug to abandon as follows:

- 100 Sacks cement - Spotted on bottom at 13,563'
- 75 sacks cement - 10,400-10,600'
- 75 sacks cement - 9,800-10,000'
- 75 sacks cement - 7,400-7,550'
- 75 sacks cement - 5,050-5,250'
- 75 sacks cement - 4,450-4,325'
- 10 sacks cement - Surface Cap

All other intervals from surface to total depth will be filled with heavy mud laded fluid.

Confirming verbal approval received from Mr. Randall Montgomery.

Approved....., 19.....  
Except as follows: NOV 20 1956

Approved  
OIL CONSERVATION COMMISSION  
By E. J. Fischer  
Title Engineer District II

Skelly Oil Company  
Company or Operator  
By [Signature]  
Position Dist. Supt.  
Send Communications regarding well to:  
Name Skelly Oil Company  
Address Box 38 - Hobbs, New Mexico

