

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

RECEIVED

DEC - 1 1950

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Cementing Salt String	X

November 29, 1950

McDonald, New Mex.

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

The Sharples Oil Corporation.....Seth Alston.....Well No. 1.....in the
Company or Operator Lease

SW $\frac{1}{4}$ SW $\frac{1}{4}$of Sec. 17.....T. 13S.....R. 35E.....N. M. P. M.,
Wildcat.....Field Lea.....County.

The dates of this work were as follows: November 27, 28, 1950

Notice of intention to do the work was (was ~~not~~) submitted on Form C-102 on November 27, 1950 19.....
and approval of the proposed plan was (was ~~not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Drilled 12 $\frac{1}{2}$ " hole to 2100; 11" hole to TD 4433. Ran Halliburton Caliper Survey to TD to determine amount of cement required to circulate. Ran Schlumberger Electric Log to TD. Ran 2214.65' 8 5/8" rd thd new 32# casing on bottom, 2224.78' 8 5/8" used 36# casing on top. Ran Baker wash down shoe on bottom and Baker M&F float collar on top of second joint. Cemented with 2500 sacks 4% jel cement followed with 100 sacks neat cement. Cement circulated. Pipe set at 4430.49 KB.

Witnessed by J.A. Lipton.....The Sharples Oil Corp. Field Supt.
Name Company Title

Subscribed and sworn before me this 30th.

day of November, 1950

John W. Pharrman
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name J.A. Lipton

Position Field Superintendent

Representing The Sharples Oil Corp.
Company or Operator

My commission expires September 26, 1953

Address P.O. Box 180: Denver, Colorado.

Remarks:

APPROVED
Date DEC 1 1950

Ray J. J. J. J.
Name
Oil & Gas Inspector
Title