



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in **QUINTUPLICATE**. If State Land submit 6 Copies

Sinclair Oil & Gas Company

(Company or Operator)

W. H. Anderson Unit

(Lease)

Well No. **1**, in **SW** $\frac{1}{4}$ of **SE** $\frac{1}{4}$ of Sec. **17**, T. **12S**, R. **36E**, NMPM.

Wildcat

Pool,

Lee

County.

Well is **1900'** feet from **East** line and **660'** feet from **South** line

of Section **17**. If State Land the Oil and Gas Lease No. is

Drilling Commenced **10:00 AM** **5/8/**, 19 **56**. Drilling was Completed **10/26/**, 19 **56**.

Name of Drilling Contractor **Warren Bradshaw Drilling Company**

Address **Tulsa, Oklahoma**

Elevation above sea level at Top of Tubing Head **1000'**. The information given is to be kept confidential until

, 19

OIL SANDS OR ZONES

No. 1, from **None** to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	184	N	304'				Surface
9-5/8"	36 & 40	N	1498'	Float	574'		Intermediate

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	13-3/8"	304'	350	Halliburton		
12-1/8"	9-5/8"	1498'	1800	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

DEW HOLE - PLUGGED AND ABANDONED

Result of Production Stimulation

Orig & Inst. **OGC**

cc: **FNR, NFD, File**

Depth Cleaned Out

7 **WORD OF DRILL-STEM AND SPECIAL TEST**

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 13794' feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing Plugged & Abandoned, 19____.

OIL WELL: The production during the first 24 hours was _____ barrels of liquid of which _____ % was
was oil; _____ % was emulsion; _____ % water; and _____ % was sediment. A.P.I.
Gravity _____.

GAS WELL: The production during the first 24 hours was _____ M.C.F. plus _____ barrels of
liquid Hydrocarbon. Shut in Pressure _____ lbs.

Length of Time Shut in _____.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.....	<u>2204</u>	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	<u>2285</u>	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	<u>2925</u>	T. Montoya.....	T. Farmington.....
T. Yates.....	<u>3030</u>	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	<u>3158</u>	T. McKee.....	T. Menefee.....
T. Queen.....	<u>3785</u>	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....		T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	<u>4390</u>	T. Granite.....	T. Dakota.....
T. Glorieta.....	<u>5877</u>	T.	T. Morrison.....
T. Drinkard.....		T.	T. Penn.....
T. Tubbs.....	<u>7298</u>	T.	T.
T. Abo.....	<u>8057</u>	T.	T.
T. Penn.....	<u>10070</u>	T.	T.
T. Miss.....	<u>13778</u>	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	155	155	Surface Sand				
155	218	63	Blue Clay				
218	925	707	Red Beds				
925	2290	1365	Red Beds & Shells				
2290	3185	895	Salt & Anhydrite				
3185	3815	630	Salt, Anhydrite, & Gypsum				
3815	4357	542	Anhydrite & Gypsum				
4357	4448	91	Anhydrite & Dolomite				
4448	4600	152	Lime and Anhydrite				
4600	7970	3370	Lime				
7970	8097	127	Lime and Shale				
8097	8173	76	Shale				
8173	8840	667	Lime and Shale				
8840	9680	840	Lime				
9680	9776	96	Lime and chert				
9776	10083	307	Lime				
10083	10121	38	Lime and shale				
10121	10169	48	Lime				
10169	10750	581	Lime and shale				
10750	10781	31	Lime and chert				
10781	12086	1305	Lime and shale				
12086	12446	360	Lime and shale				
12446	12519	73	Shale				
12519	12989	470	Shale and sand				
12989	13794	805	Lime and shale				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Simclair Oil & Gas Company
Name C. G. Confer

C. G. Confer 11/11/56
(Date)
Address 520 E. Broadway, Hobbs, New Mexico
Position or Title District Engineer