

MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, bear the work Medical is 55 begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

		Indicate Nature of Notice by Check	ding Below	
rice of Intention Change Plans		Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper	
rice of Intention Plug Well	**	Notice of Intention to Plug Back	Notice of Intention to Set Liner	
rice of Intention Squeeze		Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)	
ice of Intention Gun Perforate		Notice of Intention (Other)	Notice of Intention (Other)	
. CONSERVATION C ITA FE, NEW MEXIC		Hobbs, New Mexica (Place)	October 27, 1956	
tlemen:				
_			XXZ-11 NI- 3 in 0	
nelair Oil & O	Company or Operato	or)	Well Noininin	nit) Do
(40-acre Subdivision)	4 of Sec 17	, T, R, R	NMPM.,	1
Les	Co	ounty.		
	FU	LL DETAILS OF PROPOSED P	I AN OF WORK	
248mt 1	(FOLLO	W INSTRUCTIONS IN THE RULES		
13794 5/8430 Casing 8	•	W INSTRUCTIONS IN THE RULES	S AND REGULATIONS)	200.
5/8"CD Casing 8	4496' w/ 3	W INSTRUCTIONS IN THE RULES		200.
3/840D Casing 8	4496' w/ 3 e 305' w/ 3	w instructions in the rules 1800 Sks. Coment- Tep come 350 Sks. Circulated	s and regulations) mt behind casing @ 2000' 1/ surf	`aes,
3/8*0D Casing 6 3/8*0D Casing 11 hele with he	4496' w/ 3 0 305! v/ 3 nevy mad- 5 nine from	w instructions in the rules 1800 Sks. Coment- Top come 350 Sks. Circulated pet 50 Sk. Coment plug fre 1860 to 1825 Ft. filling	s and regulations) mt behind easing 0 2000' 1/ surf m 12222 to 12350 Ft. hele w/ heavy mid.	
5/8*OD Casing 6 3/8*OD Casing Li hele with he 25 Sk. eement aut 9 5/8*OD C	4496' w/ 3 e 305' w/ 3 evy mad- Sp plug from	w instructions in the rules 1800 Sks. Coment- Top come 350 Sks. Circulated pot 50 Sk. Coment plug fre 1460 to 4525 Ft. filling 3 575' Approx. Set 25 Sach	mt behind easing 0 2000' f/ surf m 12222 to 12350 Ft. hale w/ heavy mid. r Communt Plug in top 9 5/8"OD Cam	
3/8*OD Casing 6 3/8*OD Casing Li hele with he 25 Sk. easent ent 9 5/8*OD C	e 305! w/ 3 e 305! w/ 3 exy mak- S plug from lasing off	w instructions in the rules 1800 Sks. Coment Top come 350 Sks. Circulated pet 50 Sk. Coment plug fro 1460 to 4525 Ft. filling 3 575' Approx. Set 25 Sach in better of 13 3/8400 6	and regulations) mt behind easing 0 2000' f/ surf m 12222 to 12350 Ft. hale w/ heavy mad. c Commit Plug in top 9 5/8*00 Cam	ing.
3/8*00 Casing 6 3/8*00 Casing 11 hele with he 25 Sk. easent eut 9 5/8*00 C 25 Sk. 15 Sk.	e 305! w/ : e 305! w/ : evy mmd- S; plug from casing off : General plug s plug in to	w instructions in the rules 1800 Sks. Coment Top come 350 Sks. Circulated pet 50 Sk. Coment plug fre 4460 to 4525 Ft. filling 3 575' Approx. Set 35 8ach g in bettem of 13 3/8**OD 6 op 13 3/8**OD Casing & bett	mt behind easing 0 2000' f/ surf m 12222 to 12350 Ft. hale w/ heavy mid. r Communt Plug in top 9 5/8"OD Cam	ing.
3/8*OD Casing 6 3/8*OD Casing L1 hele with he 25 Sk. easent eut 9 5/8*OD C 2 Sinite 15 Sk.	e 305! w/ : e 305! w/ : evy mmd- S; plug from casing off : General plug s plug in to	w instructions in the rules 1800 Sks. Coment Top come 350 Sks. Circulated pet 50 Sk. Coment plug fre 4460 to 4525 Ft. filling 3 575' Approx. Set 35 8ach g in bettem of 13 3/8**OD 6 op 13 3/8**OD Casing & bett	and regulations) mt behind easing 0 2000' f/ surf m 12222 to 12350 Ft. hale w/ heavy mad. c Commit Plug in top 9 5/8*00 Cam	ing.
3/8*OD Casing 6 3/8*OD Casing L1 hele with he 25 Sk. easent eut 9 5/8*OD C 2 Sinite 15 Sk.	e 305! w/ : e 305! w/ : evy mmd- S; plug from casing off : General plug s plug in to	w instructions in the rules 1800 Sks. Coment Top come 350 Sks. Circulated pet 50 Sk. Coment plug fre 4460 to 4525 Ft. filling 3 575' Approx. Set 35 8ach g in bettem of 13 3/8**OD 6 op 13 3/8**OD Casing & bett	and regulations) mt behind easing 0 2000' f/ surf m 12222 to 12350 Ft. hale w/ heavy mad. c Commit Plug in top 9 5/8*00 Cam	ing.
3/8*OD Casing 6 3/8*OD Casing 11 hele with he 25 Sk. easent ext 9 5/8*OD C 2 Sinite 15 Sk.	e 305! w/ : e 305! w/ : evy mmd- S; plug from casing off : General plug s plug in to	w instructions in the rules 1800 Sks. Coment Top come 350 Sks. Circulated pet 50 Sk. Coment plug fre 4460 to 4525 Ft. filling 3 575' Approx. Set 35 8ach g in bettem of 13 3/8**OD 6 op 13 3/8**OD Casing & bett	and regulations) mt behind easing 0 2000' f/ surf m 12222 to 12350 Ft. hale w/ heavy mad. c Commit Plug in top 9 5/8*00 Cam	ing.
5/8*CD Casing 6 3/8*CD Casing 11 hele with he 25 Sk. coment cut 9 5/8*CD C 1 Sinik 15 Sk.	e 305! w/ : e 305! w/ : evy mmd- S; plug from casing off : General plug s plug in to	w instructions in the rules 1800 Sks. Coment Top come 350 Sks. Circulated pet 50 Sk. Coment plug fre 4460 to 4525 Ft. filling 3 575' Approx. Set 35 8ach g in bettem of 13 3/8**OD 6 op 13 3/8**OD Casing & bett	and regulations) mt behind easing 0 2000' f/ surf m 12222 to 12350 Ft. hale w/ heavy mad. c Commit Plug in top 9 5/8*00 Cam	ing.
5/8*OD Gasing 6 3/8*OD Gasing 6 11 hele with he 25 Sk. coment cut 9 5/8*OD C t spinit 15 Sk. t 15 Sk. Coment tending h' abov	e 305! w/ : e 305! w/ : evy mmd- S; plug from casing off : General plug s plug in to	W INSTRUCTIONS IN THE RULES 1800 Sks. Coment—Top come 350 Sks. Circulated pet 50 Sk. Coment plug fre 4460 to 4525 Ft. filling 3 575' Approx. Set 25 8ach g in bettem of 13 3/8*CD Casing & bett 18vel.	and regulations) mt behind easing 0 2000' f/ surf m 12222 to 12350 Ft. hale w/ heavy mad. c Commit Plug in top 9 5/8*00 Cam	ing.
5/8*OD Casing 6 3/8*OD Casing 6 11 hele with he c 25 Sk. coment cut 9 5/8*OD C t Minitt 15 Sk. coment to 15	e 305! w/ : e 305! w/ : exy mmd- S; plug from casing off : General plug s plug in to	W INSTRUCTIONS IN THE RULES 1800 Sks. Coment—Top come 350 Sks. Circulated pet 50 Sk. Coment plug fre 4460 to 4525 Ft. filling 3 575' Approx. Set 25 8ach g in bettem of 13 3/8*CD Casing & bett 18vel.	and regulations) mt behind easing 0 2000' f/ surf m 12222 to 12350 Ft. hale w/ heavy mad. c Commit Plug in top 9 5/8*00 Cam	ing.
3/8*OD Casing 6 3/8*OD Casing 6 11 hele with he 25 Sk. coment cut 9 5/8*OD C 26 Sk. coment cut 9 5/8*OD	e 305! w/ : e 305! w/ : e 305! w/ : plug from casing off : General plug s plug in to consultate con	W INSTRUCTIONS IN THE RULES 1800 Sks. Coment—Top come 350 Sks. Circulated pet 50 Sk. Coment plug fre 4460 to 4525 Ft. filling 3 575' Approx. Set 25 8ach g in bettem of 13 3/8*CD Casing & bett 18vel.	and regulations) mt behind easing 0 2000' f/ surf m 12222 to 12350 Ft. hale w/ heavy mad. c Commit Plug in top 9 5/8*00 Cam	ing.
3/8*CD Casing 11 hale with he 25 Sk. coment out 9 5/8*CD C 2 Shuffk 15 Sk. 2 15 Sk. Coment centing 4' abov	e 305! w/ : e 305! w/ : exy mmd- S; plug from casing off : General plug s plug in to	W INSTRUCTIONS IN THE RULES 1800 Sks. Coment Pop sense 350 Sks. Circulated pet 50 Sk. Coment plug fre 4460 to 4525 Ft. filling 3 575' Approx. Set 25 Sach g in bettem of 13 3/8*CD (op 13 3/8*CD Casing & bett 18vel. By	mt behind easing # 2000' f/ surfunt behind easing # 2000' f/ surfunt light to p 9 5/8"OD Can leading. Simpley of operator Company of operator Company of operator	ing.