

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<input checked="" type="checkbox"/>		

Hobbs, New Mexico

9/27/38

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

DUPLICATE

Following is a report on the work done and the results obtained under the heading noted above at the
Tide Water Assoe Oil Company. State **"L"** Well No. **1** in the
Company or Operator **Hwt** Lease **12**

Tatum Area of Sec. **23**, T. **12**, R. **36**, N. M. P. M.,
Field, **Lea** County

The dates of this work were as follows: **9/16/38**Notice of intention to do the work was (~~XXXX~~) submitted on Form C-102 on **9/20/38**and approval of the proposed plan was (~~XXXX~~) obtained. (Cross out incorrect words.)

HOBBS OFFICE

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Well had been plugged from 5294' to 5150' w/45-sacks cement and filled w/ heavy mud to 3300', and 35-sacks cement from 3300' to 3235', shot and tested brown lime from 3210' to 3230' and it tested dry. Filled up with heavy mud to 1000' and cemented w/15-sacks cement and filled back up to 300' w/mud and cemented w/15-sacks cement, then filled up to surface with heavy mud and cemented top of surface casing with regulation marker erected. The location was then cleaned up and leveled. The 8-5/8" OD Casing was shot off at 1000' and pulled.

Witnessed by **Loyd Lamb** **Tide Water Assoe Oil Company.** Foreman
Name Company Title

Subscribed and sworn before me this

27 day of **September**, 19 **38***Lance Sparks*

Notary Public

My commission expires **November 22, 1941.**

I hereby swear or affirm that the information given above is true and correct.

Name **Elmer Lamb - P.P.**Position **Prod. Sup't**Representing **Tide Water Assoe Oil Company.**
Company or OperatorAddress **Drawer KK, Hobbs, New Mexico.**

Remarks:

[Signature]
Name
OIL & GAS INSPECTOR
Title

