

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____ 2260	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 3023	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____ 3176	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 4420	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____ 5860	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____ 7110	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____ 7730	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____ 9045	T. _____	T. Chinle _____	T. _____
T. Penn. _____ 9690	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	324	324	Surf. S & C.				
324	630	306	Clay				
630	1277	647	Red Bed				
1277	1907	630	Red Bed Anhy				
1907	4422	2515	Anhy & gyp.				
4422	6418	1996	Lime				
6418	7468	1050	Lime & shale				
7468	8217	649	Lime				
8217	9120	903	Lime & Shale				
9120	9174	54	Lime, shale & chert				
9174	9369	195	Lime, Shale				
9369	9478	109	Lime				
9478	9500	22	Lime & shale				
9500	9650	150	Lime				
9650	9742	92	Lime & shale				
9742	9768	26	Lime				
9768	10010	242	Lime & shale				