

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

Orig & cc: NEW MEXICO OIL CONSERVATION COMMISSION  
 cc: OCC, Hobbs  
 cc: Southern Region (West Texas)  
 cc: file

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator SINCLAIR OIL CORPORATION	8. Farm or Lease Name John Shults
3. Address of Operator P. O. Box 1920, Hobbs, New Mexico 88240	9. Well No. 2
4. Location of Well UNIT LETTER <u>P</u> <u>660</u> FEET FROM THE <u>East</u> LINE AND <u>330</u> FEET FROM THE <u>South</u> LINE, SECTION <u>13</u> TOWNSHIP <u>12S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat Gladiola
15. Elevation (Show whether DF, RT, GR, etc.) 3881' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input checked="" type="checkbox"/> Plugback, perf. & treat lower Abo.	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD Drilled 10,010. PBTD 9650'. Presently completed in Wolfcamp perms. 9604-9616'

PROPOSE TO: Set CIBP in 5-1/2" OD csg @ 9080' w/2 sacks cement on plug, test casing & plug.  
 Perf. lower Abo at intervals approx. 8975-8994' and 9010-9020' w/2-3/8" holes  
 per. foot. Acidize w/approx. 3000 gals. inhibited LST acid, swab to test.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Superintendent DATE 1-7-69  
 APPROVED BY John W. Banyan TITLE Geologist DATE JAN 8 1969  
 CONDITIONS OF APPROVAL, IF ANY: