

**NEW MEXICO OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico

**MISCELLANEOUS NOTICES**

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>X</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Midland, Texas  
(Place)

June 5, 1959  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Monterey Oil Company C. C. Selman Well No. 1 in 0  
(Company or Operator) (Lease) (Unit)  
SW 1/4 SE 1/4 of Sec. 22, T. 12-N, R. 27-E, NMPM, Wildcat Pool  
(40-acre Subdivision)  
Lee County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

**Condition of Well Before Plugging**

1. 13-3/8", 48#, H-40 casing cemented at 367' with 375 sx. neat (circulated to surface) in 17-1/2" hole.
2. 8-5/8", 24#, J-55 and 32# (J-55 & H-40) casing cemented at 4500' with 500 sx. neat in 12-1/4" (367-1750') and 11" hole (1750-4500'). Calculated top of cement at 2337'.
3. 7-7/8" open hole (4500 - 12,584' T.D.).

10,860' and 11,470'.

2. Place 35 sx. neat plug in and out of 8-5/8" casing at 4500'.
3. Shoot and remove 8-5/8" casing above 1700' (free point).
4. Place 25 sx. neat plug in and out of 13-3/8" casing at 367' and 10 sx. neat plug at surface with steel plate welded to 13-3/8" casing.
5. Leave 9# mud in hole.
6. Plugging date: 4-28-59.

**Proposed Plugging Procedure**

1. Place 25 sx. neat plugs in open hole at

★ Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

Monterey Oil Company

Company or Operator

By..... R. P. Brewer R. P. Brewer

Position..... Petroleum Engineer  
Send Communications regarding well to:

Name..... Monterey Oil Company

Address..... 6th Floor Wilco Bldg., Midland, Texas

★ Program outlined above approved by Oil Conservation Commission in 5-27-59 letter.