

NEW MEXICO OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Form C-110  
Revised 7/1/55

(File the original and 4 copies with the appropriate district office)

CERTIFICATE OF COMPLIANCE AND AUTHORIZATION  
TO TRANSPORT OIL AND NATURAL GAS

Company or Operator Pan American Petroleum Corporation Lease Leis Wingard

Well No. 3 Unit Letter A S 24 T 12 R 37 Pool Gladiola Wolfcamp

County Lea Kind of Lease (State, Fed. or Patented) Patented

If well produces oil or condensate, give location of tanks: Unit B S 24 T 12 R 37

Authorized Transporter of Oil or ~~Condensate~~ Service Pipe Line Company

Address Box 357 Midland, Texas

(Give address to which approved copy of this form is to be sent)

Authorized Transporter of Gas \_\_\_\_\_

Address \_\_\_\_\_

(Give address to which approved copy of this form is to be sent)

If Gas is not being sold, give reasons and also explain its present disposition:

Vented - No marketing facilities available.

Reasons for Filing: (Please check proper box) New Well \_\_\_\_\_ ( )

Change in Transporter of (Check One): Oil ( ) Dry Gas ( ) C'head ( ) Condensate ( )

Change in Ownership \_\_\_\_\_ ( ) Other \_\_\_\_\_ (x)

Remarks: \_\_\_\_\_ (Give explanation below)

Change of operating name from "Stanolind Oil and Gas Company" to  
"Pan American Petroleum Corporation" effective February 1, 1957.

The undersigned certifies that the Rules and Regulations of the Oil Conservation Commission have been complied with.

Executed this the 25th day of January 19 57

By Ralph H. Henningsen

Approved JAN 29 1957 19 \_\_\_\_\_

Title Field Superintendent

Company Pan American Petroleum Corporation

OIL CONSERVATION COMMISSION

Address Box 68

By E. J. Fischer

Title Engineer District 1

Hobbs, New Mexico

The following table shows the results of the experiment. The first column is the time in seconds, the second column is the distance in meters, and the third column is the velocity in meters per second.

Time (s)	Distance (m)	Velocity (m/s)
0.0	0.0	0.0
0.5	0.5	1.0
1.0	1.0	2.0
1.5	1.5	3.0
2.0	2.0	4.0
2.5	2.5	5.0
3.0	3.0	6.0
3.5	3.5	7.0
4.0	4.0	8.0
4.5	4.5	9.0
5.0	5.0	10.0
5.5	5.5	11.0
6.0	6.0	12.0
6.5	6.5	13.0
7.0	7.0	14.0
7.5	7.5	15.0
8.0	8.0	16.0
8.5	8.5	17.0
9.0	9.0	18.0
9.5	9.5	19.0
10.0	10.0	20.0