

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 20, 1953

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil and Gas Company

(Company or Operator)

Lois Wingerd

(Lease)

Company Rig #8

(Contractor)

Well No. 6 in the NE 1/4 SE 1/4 of Sec. 24

T. 26, R. 37, NMPM., Gladiola Pool, Lea County.

The Dates of this work were as follows: 4-13-53 to 4-15-53 Inclusive.

Notice of intention to do the work (X) (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)

and approval of the proposed plan (X) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On April 13, 1953 ran 4479' of 9-5/8" casing landed at 4500' with staging collar set at 2280'. Cemented 1st Stage with 440 sacks cement mixed with 8% gel plus 100 sacks neat. Cemented 2nd stage with 150 sacks neat cement. Completed 3:40 P. M. 4-14-53. Temperature survey indicated top of cement 1850', after 30 hours tested 9-5/8" casing before drilling plug with 1100 psi. Tests O. K. Drilled D. V. tool and cement to top of float collar and tested with 1100 psi for 30 minutes. Tests O. K. Drilled float collar, firm cement and float shoe to 4502' and tested with 1100 psi for 30 minutes. Test O. K. Drilling operations were resumed.

Witnessed by R. L. St. Clair Stanolind Oil and Gas Company Tool Pusher
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

Roy Yarkrough
(Name)

(Title)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: Ralph H. Henneman

Position: Field Superintendent

Representing: Stanolind Oil and Gas Company

Address: P. O. Box 68, Hobbs, New Mexico

APR 28 1953

(Date)

