


DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico



MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

October 6, 1953 Hobbs, New Mexico
(Date) (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil and Gas Company Lois Wingerd
(Company or Operator) (Lease)
Loffland Brothers Company, Well No. 9 in the NE 1/4 SE 1/4 of Sec. 24,
(Contractor)
T. 12-S, R. 37-E, NMPM, Gladiola - Wolfcamp Pool, Lea County.

The Dates of this work were as follows: October 3, 1953 to October 5, 1953 Inclusive.

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)
and approval of the proposed plan ~~was~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On October 3, 1953 ran 4488' of 9-5/8" casing landed at 4499' with D. V. tool set at 2286' Cemented first stage with 440 sx 8% gel followed with 100 sx. neat cement. Cemented second stage with 150 sx. neat cement. After 36 hours W. O. C. tested 9-5/8" casing above D. V. tool with 1000 psi for 30 minutes with no loss in pressure. Drilled D. V. tool and tested casing with 1000 psi for 30 minutes with no drop in pressure. Drilled plug and firm cement to casing shoe and tested casing with 1000 psi for 30 minutes and as there was no drop in pressure drilling operations were resumed.

Witnessed by T. J. Thigpen Stanolind Oil and Gas Company Farm Boss
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

J. G. Stanley
(Name)
Engineer District 1 OCT 13 1953
(Title) (Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: *Ralph Lenduckson*
Position: Field Superintendent
Representing: Stanolind Oil and Gas Company
Address: Box 68, Hobbs, New Mexico

