

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL AND GAS COMMISSION

MAR 23 1 00 PM '66

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Jake L. Hamon	8. Farm or Lease Name H. R. Fields
3. Address of Operator P.O. Box 663, Dallas, Texas 75221	9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>330</u> FEET FROM THE <u>North</u> LINE AND <u>467</u> FEET FROM THE <u>East</u> LINE, SECTION <u>25</u> TOWNSHIP <u>12 S</u> RANGE <u>37 E</u> NMPM.	10. Field and Pool, or Wildcat Gladiola (Devonian)
15. Elevation (Show whether DF, RT, GR, etc.) 3872.7' Gr.	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 25 sk. cement plug in bottom of 5½" casing from 11,733' to 11,953' to seal off perforations from 11,940' to 11,950'.

Shoot and pull 5½" casing as deep as possible.

Set 25 sk. cement plug 50' in and 50' out of stub of 5½" casing.

If 5½" casing is pulled deeper than the following depths, then a 25 sk. cement plug will be set at each of these places with drilling mud placed between the plugs:

Base of San Andres or top of Glorieta at 5655'.

Top of Tubbs at 5690'.

Top of Abo at 7132'.

Top of Penn at 9610'.

Set 30 Sk. cement plug 50' below and 50' in base of 9 5/8" casing at 4516' from 4566' to 4466'.

Set 10 sk. cement plug in top of 9 5/8" casing which will be a 25' plug.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Cecil H. Baston TITLE Petroleum Engineer DATE March 22, 1966

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: