

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

FORM C-103
(Rev 3-55)

MISCELLANEOUS REPORTS ON WELLS

(Submit to appropriate District Office as per Commission Rule 1106)

Name of Company Amerada Petroleum Corporation		Address Roswell Star Route - Tatum, New Mexico																			
Lease Brady Low	Well No. 1	Unit Letter C	Section 34	Township 12-S	Range 37-E																
Date Work Performed 8-24 to 8-28-61	Pool Undesignated	County Lea																			
THIS IS A REPORT OF: (Check appropriate block)																					
<input type="checkbox"/> Beginning Drilling Operations		<input type="checkbox"/> Casing Test and Cement Job		<input type="checkbox"/> Other (Explain):																	
<input checked="" type="checkbox"/> Plugging		<input type="checkbox"/> Remedial Work																			
Detailed account of work done, nature and quantity of materials used, and results obtained. Authority to P & A Received by Telephone Conversation to Mr. Eric F. Engbrecht. Total Depth Drilled 12,404', Well Plugged and Abandoned effective 8-28-61. Plugs set as following: <table border="1"> <thead> <tr> <th>No. Sacks</th> <th>Depth</th> </tr> </thead> <tbody> <tr> <td>35 Sx. Slo-Set</td> <td>12,276' to 12,380' in 7-7/8" Open Hole</td> </tr> <tr> <td>35 "</td> <td>11,526' to 11,630' "</td> </tr> <tr> <td>35 "</td> <td>9481' to 9585' "</td> </tr> <tr> <td>35 "</td> <td>9021' to 9125' "</td> </tr> <tr> <td>35 "</td> <td>7800' to 7904' "</td> </tr> <tr> <td>35 "</td> <td>5820' to 5924' "</td> </tr> <tr> <td>35 "</td> <td>4353' to 4465' Inside 8-5/8" OD Casing.</td> </tr> </tbody> </table> Shot off 8-5/8" OD Casing @ 837' & Pulled 20 jts for 825', spotted 50 Sx. Regular Cement in & out top 8-5/8" OD Shot off casing from 773' to 868' & 50 Sx. Regular Cement in and out bottom 13-3/8" OD Casing from 278' to 341', spotted 15 Sx. Regular Cement in top 13-3/8" OD Casing & Installed Dry Hole Marker. Hole filled with drilling mud between all plugs.						No. Sacks	Depth	35 Sx. Slo-Set	12,276' to 12,380' in 7-7/8" Open Hole	35 "	11,526' to 11,630' "	35 "	9481' to 9585' "	35 "	9021' to 9125' "	35 "	7800' to 7904' "	35 "	5820' to 5924' "	35 "	4353' to 4465' Inside 8-5/8" OD Casing.
No. Sacks	Depth																				
35 Sx. Slo-Set	12,276' to 12,380' in 7-7/8" Open Hole																				
35 "	11,526' to 11,630' "																				
35 "	9481' to 9585' "																				
35 "	9021' to 9125' "																				
35 "	7800' to 7904' "																				
35 "	5820' to 5924' "																				
35 "	4353' to 4465' Inside 8-5/8" OD Casing.																				
Witnessed by		Position Assist. Dist. Super.		Company Amerada Petroleum Corporation																	
FILL IN BELOW FOR REMEDIAL WORK REPORTS ONLY																					
ORIGINAL WELL DATA																					
D F Elev.	T D	P B T D	Producing Interval		Completion Date																
Tubing Diameter		Tubing Depth		Oil String Diameter	Oil String Depth																
Perforated Interval(s)																					
Open Hole Interval			Producing Formation(s)																		
RESULTS OF WORKOVER																					
Test	Date of Test	Oil Production BPD	Gas Production MCFPD	Water Production BPD	GOR Cubic feet/Bbl	Gas Well Potential MCFPD															
Before Workover																					
After Workover																					
OIL CONSERVATION COMMISSION				I hereby certify that the information given above is true and complete to the best of my knowledge.																	
Approved by <i>Lester A. Clements</i>				Name <i>W. H. Hamilton</i>																	
Title				Position Assistant District Superintendent																	
Date				Company Amerada Petroleum Corporation																	

Roswell Star Route - Tatum, New Mexico