

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy <u>2210</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>11,127</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>3082</u>	T. Miss <u>11,478</u>	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian <u>12,218</u>	T. Menefee _____	T. Madison _____
T. Queen <u>3840</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>4465</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta <u>5920</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard <u>7200</u>	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo <u>7892</u>	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp <u>9233</u>	T. _____	T. Chinle _____	T. _____
T. Penn. <u>9554</u>	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	2210	2210	Red Beds & Sands				
2210	3082	872	Anhydrite & Salt				
3082	4465	1383	Sand, Shale & Anhydrite				
4465	5920	1455	Dolomite				
5920	7892	1972	Sands & Dolomite				
7892	9233	1341	Shale & Dolomite				
8233	11127	1894	Lime & Shale				
11127	11478	351	Sands & Shales				
11478	12138	660	Lime & Chert				
12138	12218	80	Shale				
12218	12230	12	Dolomite				