

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

RECEIVED

DEC 14 1951

OIL CONSERVATION COMMISSION
HOBBS-OFFICE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

The Devonian Company Lea State "J"

Company or Operator

Lease

Well No. 1 in NW NW of Sec. 12 T. 13S

R. 37E N. M. P. M., Wildcat Field, Lea County.

Well is 660 feet south of the North line and 660 feet East of the East line of Section 12

If State land the oil and gas lease is No. B-9122 Assignment No. B-9122-1

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is The Devonian Company Address Box 1379 - Tulsa, Okla.

Drilling commenced May 6 1951 Drilling was completed November 5, 1951

Name of drilling contractor Parker Drilling Company Address Tulsa, Oklahoma

Elevation above sea level at top of casing 3881 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from Completed to Dry No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13-3/8"	48#	8 R.T.	SS	372'				
9-5/8"	40,36#	8 R.T.	SS	4652'		Pulled 1163.69'		
7"	29,26,23#	8 R.T.	SS	9685'		Pulled 8652.		

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/4"	13-3/8"	389'	370	Howe		
12-1/4"	9-5/8"	4668'	2000	Howe		
8-3/4"	7"	9699'	110	Howe		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		15% NE	2000 Gals	11-18-51	9600-9625'	
		15% NE	500 Gals	11-20-51	9600-9625'	
		15% NE	1000 Gals	11-22-51	9600-9625'	
		15% NE	2000 Gals	11-26-51	9600-9625'	

Results of shooting or chemical treatment.

None

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 12,603 feet, and from feet to feet.

Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to producing Completed dry, 19

The production of the first 24 hours was barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Parker Drilling Company

Driller Driller

Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

DEC 12 1951

Place Date

Name E. S. Stewart

Position PRESIDENT

Representing THE DEVONIAN COMPANY

Company or Operator.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0'	14.79'		Top Kelly Bushing to Top of Ground
	310'		Surface
	425		Red Bed
	1895		Red Bed and Shale
	2185		Red Bed
	2395		Red Bed and Anhydrite
	3233		Red Bed and Salt
	3499		Red Bed
	3620		Red Bed
	3690		Anhydrite
	3691		Anhydrite
	4179		Anhydrite and Red Bed
	4203		Anhydrite
	4608		Red Bed and Anhydrite
	5103		Lime
	4994		Lime
	5226		Chert and Lime
	8575		Lime
	8621		Lime
	8737		Lime and Shale
	8832		Lime and Anhydrite
	9258		Belomite and Shale
	9297		Lime
	9353		Lime and Anhydrite
	9520		Lime
	9546		Lime and Chert
	9565		Lime
	9570		Lime and Chert
	9634		Lime
	9643		Lime and Chert
	9858		Lime
	9879		Lime and Shale
	10068		Lime
	10125		Lime and Shale
	10168		Lime
	10215		Lime and Shale
	10312		Lime
	10322		Belomite
	10465		Lime
	10491		Lime and Shale
	11045		Lime
	11062		Lime and Chert
	11090		Lime
	11121		Lime and Shale
	11390		Lime
	11353		Lime and Chert
	11388		Lime
	11413		Lime and Shale
	11442		Lime
	11456		Lime and Shale
	11496		Lime
	11563		Lime and Shale
	11586		Lime
	11856		Lime and Shale
	12016		Lime and Chert
	12038		Lime, Shale and Chert
	12118		Lime and Shale
	12132		Lime
	12398		Lime and Shale
	12424		Sand, Lime and Shale
	12434		Sandy Lime and Shale
	12444		Lime and Shale
	12456		Sand, Lime and Shale
	12603 TD		Lime and Shale