

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Cabot Petroleum Corporation	8. Farm or Lease Name Howard Fleet
3. Address of Operator P. O. Box 5001, Pampa, TX 79065	9. Well No. 2
4. Location of Well UNIT LETTER <u>P</u> <u>330</u> FEET FROM THE <u>East</u> LINE AND <u>990</u> FEET FROM THE <u>South</u> LINE, SECTION <u>35</u> TOWNSHIP <u>13S</u> RANGE <u>37E</u> N.M.P.M.	10. Field and Pool, or Wildcat King Devonian
15. Elevation (Show whether DF, RT, GR, etc.) 3852' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input checked="" type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 6/19/85 pulled 43 jts of 5 1/2" casing and installed 66 jts. of 5 1/2" 17# J-55 & N-80 LT&C casing, set at 2703'. Drilled out CIBP at 12,495' and wash to bottom at 12,625'. Circ. & Cond. hole, dump 2 sxs sand at 9547'. Perf. 4 holes at 4635', pump 200 sxs Class 'C' cement, squeeze to 500#, top of cement 4364' between 5 1/2" & 8 5/8". Test squeeze perf. @ 4635' w/575#. Install Reda pump and return to production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Jerry Sexton* TITLE Agent DATE 8/16/85

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT SUPERVISOR

APPROVED BY _____ TITLE _____ DATE AUG 20 1985

CONDITIONS OF APPROVAL, IF ANY: