Cabot H. L. Lowe "C" No.1	Houston Oil Co. of Texas State "AB" No. 1 (Orig drld by Cities Service & P&A)	OPERATOR Lease/Well No.
0 26-13-37 4/1/58	as D 36-13-37 7/21/52 4/1/53	Location USTR
4/1/58	7/21/52 4/1/53	Type & Date Drilled
12750	11570 10820	T.D.
17-1/4" 12-1/2" 7-7/8"	17-1/2" 12-1/4" 7-7/8"	Hole Size
13-3/8"-48# 8-5/8"-32&24# 5-1/2"-17&20#	13-3/8"-35.6# 9-5/8"-32# 5-1/2"-17#	Size & Wt.
363 4630 11565	334 4644 10820	Casing Depth
400 sx 2400 sx 600 sx	300 sx 2395 sx 200 sx	Cement
Circ 215' 8750(T.S.)	Circ Girc 9223'(Calc)	TOC
$\frac{4/1/58}{10000-10037, ac/1500 gal}{10000-10037, ac/1500 gal}{10000-10037, ac/1500 gal}{10000-10037, ac/1500 gal}{1000000000000000000000000000000000000$	7/52 -Drilled & abandoned by CitiesService. $4/1/53$ - Houston Oil reentered& ran $5-1/2$ ", set @ 10820', cmtd w/200 sxof 6% Gel, reg Halliburton cement(Longhorn), PBTD 10,741' $4/5/53$ - Perf10538-10582' & 10592-10598', AC/885 MCA,swb 16 hrs, S.O.& G. Rev out 800' oil &150' Ac. wtr. $4/9/53$ - Reperf 10538-10582'AC/2000 MCA & 6000 reg. 5.3 BPM,B.D. @ 4400#,M.P. 5000#. Swb 3 BFPH (70%)oil) until well swabbed dry. $4/16/53$ - Perf 10682-10696', Ac/250 MCA& 1500 reg. Broke 6100# to 3400#. Pkr was@ 10606'. Swb dry-no recovery out of Fmn. $4/19/53$ - Perf 10510-10538', Ac/250 MCA,3000 channel Ac, 12000 reg 5200#-4900#.Final: swb until 4/30/53. Avg 4 BFPH, FLlowered to 9500'. $5/27/53$ - Plugged back10696 to 10500'w/25 sx, cut & pulled7501' of $5-1/2$ ", plgd 4670 to 4594'w/25 sx, 10 sx @ top. P&A. See attachedsketch.	Remarks

MAR 20 1988