

Current Wellbore

CABOT PETROLEUM CORPORATION

J.L. REED NO. 3

1980 FNL & 1650 FEL

Unit G, Section 35, T13S, R37E
Lea County, New Mexico

Elev. 3847.9 GR

3860.9 KB

13 3/8" 48# H-40
@ 360' 400SX
Cmt. CIRC

8 5/8" 24# & 32#
@ 4583'
2400SX, Cmt. CIRC.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH

Southeastern New Mexico

T. Anhy.....	2,175	T. Devonian.....	12,160
T. Salt.....	2,280	T. Silurian.....	
B. Salt.....	3,060	T. Montoya.....	
T. Yates.....	3,120	T. Simpson.....	
T. 7 Rivers.....		T. McKee.....	
T. Queen.....		T. Ellenburger.....	
T. Grayburg.....		T. Gr. Wash.....	
T. San Andres.....	1,565	T. Granite.....	
T. Glorieta.....	6,050	T.	
T. Drinkard.....		T.	
T. Tubbs.....	7,298	T.	
T. Abo.....	7,975	T.	
T. Perm.	11,085	T.	
T. Miss.....	11,115	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To
0	360	360	Surface Sand & Gravels		
360	2175	1815	Red beds, Sh. & Li e		
2175	2280	105	Anhydrite		
2280	3120	840	Salt & Anhydrite		
3120	1565	1115	Sand, Sh. Lins & Anhydrite		
1565	6050	1115	Dolomite & Anhydrite		
6050	7975	1925	Sand, Shale & Dolomite		
7975	9000	1025	Anhydrite, Shale & Dolomite		
9000	11085	2085	Dolomite, Lins, Sh., & Chert		
11085	11115	330	Sand, Shale & Lins		
11115	12057	642	Lins and Chert		
12057	12160	103	Shale and Lins		
12160	12130	270	Dolomite and Lins		

25 SX Cmt Plug
at 5 1/2" CSG stub
@ 5650'

Top Cmt @ 8035'
Temp. Surv.

WOLF CAMP Perf.
9345-57, 9360-64,
9368-72, 9406-16

50 SX Cmt Plug
across Perf 9345-9416'

← 9850' CIRC w/2SX Cmt. on top

5 1/2" 17,20,23# N-80
@ 12,300' 700SX.
Cmt Top @ 8035' Surv.

DEVONIAN Perf: 12190'-201, 12207-25
12250-56, 12267-83
12300-305

DEV. OPEN HOLE 12300'-12430'

TD 12430'