

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	X	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 25, 1953
(Date)Tatum, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation
(Company or Operator)Lois C. Hobbs
(Lease)Noble Drilling Corporation
(Contractor)

Well No. 1 in the NW 1/4 NW 1/4 of Sec. 3

T. 14-S, R. 37-E, NMPM, Wilcox

Pool, Lea County.

The Dates of this work were as follows: June 25, 1953

Notice of intention to do the work (was) ~~same~~ submitted on Form C-102 on June 23, 1953,
(Cross out incorrect words)and approval of the proposed plan ~~was~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

11,754' Total Depth. Lins. Ran Schlumberger surveys to depth of 11,710'. Finished drilling 7-7/8" hole to 11,754' @ 10:00 AM on 6/22/53. To plug and abandon well filled hole with heavy drilling mud from 11,754' to 9850' and spotted a 35 sack cement plug from 9736' to 9850'; filled hole with drilling mud and spotted 35 sack cement plug from 6172' to 6286'; filled hole with mud and spotted a 35 sack cement plug from 4701' to 4815'. Ran McCullough Jet Casing Cutter and cut 8-5/8" casing @ 2251' - casing would not pull free. Ran McCullough casing cutter to 1616' and cut 8-5/8" casing - casing would not pull free. Ran McCullough casing cutter to 1387' and cut 8-5/8" casing - casing would not pull free. Ran Dia-Log Free Point Indicator - found casing free @ 899' - cut casing @ 894' and pulled 29 jts - 870' of 8-5/8" OD casing. Filled hole with drilling mud and spotted 15 sack cement plug from 348' to 367'; filled hole with mud and spotted 10 sack cement plug from 0' to 10' in top of 13-3/8" OD casing; plugging completed @ 12:30 AM on 6/25/53. A piece of 4" line pipe placed in cement to extend 5' above ground level.

Witnessed by R. J. Brakey
(Name)Amerada Petroleum Corporation
(Company)Farm Boss
(Title)

Approved:

OIL CONSERVATION COMMISSION

Oil & Gas Inspector

(Title)

SEP 2 1953
(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation

Address Roswell Star Route Tatum, New Mexico

