

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPPLICATE to the District Office, Oil Conservation Commission, before the work is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the objection of the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOTatum, New Mexico  
(Place)June 23, 1953  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation

Lois C. Hobbs

Well No. 1

in "D"

(Company or Operator)

(Unit)

NW/ 1/4 NW/ 1/4 of Sec. 3  
(40-acre Subdivision)

T. 14-S

R. 37-E

NMPM,

Wildcat

Pool

Lea

County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

11,754' Total Depth. Line. Ran a drill stem test from 11,591' to 11,754' . Tool was open 1 hour and 5 minutes. No fluid or gas to surface. Recovered 2700' of water blanket and 30' of drilling mud. No show of gas, oil or formation water. Ran Schlumberger surveys to depth of 11,710'. It is our intention to plug and abandon the above well. The following procedure will be effected: Spot a 35 sack cement plug from 9736' to 9850' after filling hole with heavy drilling mud; fill hole with drilling mud and spot a 35 sack cement plug from 6172' to 6286'; fill hole with mud and spot a 35 sack cement plug from 4701' to 4815'; run McGullough jet cutter and cut off 8-5/8" casing @ approximately 2250' and salvage casing above that point. Fill hole with drilling mud and spot a 15 sack cement plug from 361' to 370', fill hole with mud and spot a 10 sack cement plug from 0' to 10' in top of 13-3/8" OD casing. A piece of 4" pipe will be cemented in the top of 13-3/8" casing extending 5' above ground level to serve as a marker.

Approved....., 19.....  
Except as follows:Amerada Petroleum Corporation  
Company or Operator

By

Position..... Assistant District Superintendent  
Send Communications regarding well to:Approved  
OIL CONSERVATION COMMISSION

By

Title

Engineer Dist.

Name..... Amerada Petroleum Corporation

Address..... Roswell Star Route Tatum, New Mexico

