

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

**NEW MEXICO OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico

**MISCELLANEOUS NOTICES**

Submit this notice in **TRIPPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>X</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Andrews, Texas  
(Place)

November 30, 1964  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation M. M. Harris Well No. 2 in D  
(Company or Operator) (Unit)  
NW 1/4 NW 1/4 of Sec. 8, T-12-S, R-35-E, NMPM, Gladiola Pool  
(40-acre Subdivision)  
Lee County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to plug and abandon this well by the following procedure:

1. Spot 100' cement plug at bottom of hole 12,040-11,940' to cover perfs 12,020-12,040'
2. Shoot 5 1/2" OD casing off at 10,000' (cement top at 10,055') and pull same.
3. Spot mud from bottom plug at 11,940' to surface then spot cement plugs at following intervals:
  - 9950 - 10050' across severed casing
  - 9003 - 9103' across Hueco fm top @ 9053'
  - 7764 - 7864' across Abo fm top @ 7814'
  - 7090 - 7190' across Tubb fm top @ 7140'
  - 5850 - 5950' across Glorietta fm top @ 5878'
  - 4447 - 4547' across 9 5/8" OD casing shoe @ 4497' (9 5/8" casing has cement behind it to surface)

Surface to 50'

4. Remove tubing and casing heads; install 4" pipe marker into top of hole extending 4' above ground level.
5. Clear and level location, including cutting off holddowns to 18" below surface.

**SEE ATTACHED LETTER FOR OFFSET OPERATORS**

Approved....., 19.....  
Except as follows:

**GULF OIL CORPORATION**

Company or Operator

By.....

Position..... **Area Engineer**

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

Name **Fred G. Courtney**

Address **P.O. Box 98; Andrews, Texas**