

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

(Form C-103)
(Revised 7/1/62)

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

1963 JUL 3 PM 3:10

Submit this notice in **TRIPPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Andrews, Texas

July 1, 1963

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation **M. M. Harris** Well No. **4** in **F**
(Company or Operator) (Unit)
SE 1/4 NW 1/4 of Sec. **8**, T-**12-S**, R-**38-E**, NMPM, **Gladiola Devonian** Pool
(40-acre Subdivision)
.....County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Reference our C-103 this well for work performed 6/3-8/63. It is proposed that this well be plugged and abandoned in the following manner:

1. Recover approximately 4000' of 5 1/2" OD casing.
2. Spot 100' cement plug at point where 5 1/2" OD casing will be severed, 50' below and 50' on top of such point.
3. Spot 50' cement plug at top of well in 9 5/8" OD casing (cement was circulated to surface when 9 5/8" OD casing was run and set at 4500').
4. Leave 4" pipe marker in top cement plug, extending 4' above ground level.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

GULF OIL CORPORATION

Company or Operator

By *J. L. M. Bell*

Position **Petroleum Engineer**

Send Communications regarding well to:

GULF OIL CORPORATION

Name.....

Address **Box 98; Andrews, Texas**