

NUMBER		COPIES RECEIVED	
DISTRIBUTION			
SANTA FE			
FILE			
U.S.G.S.			
LAND OFFICE			
TRANSPORTER	OIL		
	GAS		
PRODUCTION OFFICE			
OPERATOR			

(Form C-102)
(Revised 7/1/62)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

HOBBS OFFICE O. C. C.
JUL 22 10 10 AM '64

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL and abandon	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Midland, Texas
(Place)

July 20, 1964
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Signal Oil and Gas Company S. P. Johnson Well No. 1 in E
(Company or Operator) (Unit)
SW $\frac{1}{4}$ NW $\frac{1}{4}$ of Sec. 17, T. 12-S, R. 38-E, NMPM, Gladiola Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Present Status

Total Depth 11,995'
Perforations None
Open hole 11,989' - 11,995'

Casing	Depth	Top Cement
13 3/8"	305'	Surface
8 5/8"	4595'	Surface
5 1/2"	11,989'	10,500 EST

Program

1. Place Bridge Plug @ 11,000' and cap with 1 sack cement.
- *2. Part 5 1/2" casing @ 5000' + and pull.
3. Place 35 sack cement @ casing stub.
4. Place 25 sack cement @ 4595'.
5. Place 25 sack cement @ surface with required marker.

*In the event more than 5000' of 5 1/2" casing is recovered, 25 sack plugs will be placed at the top of the Glorieta, Tubbs and Abo formations as necessary.

Approved....., 19.....
Except as follows:

Signal Oil and Gas Company
Company or Operator

By D. J. Delany J. Delany

Position Production Engineer
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By [Signature]

Title.....

Name A. G. Ambler, District Superintendent
Signal Oil and Gas Company
Address 509 W. Texas Ave., Midland, Texas