

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Orig&2cc: OCC, Hobbs
cc: Regional Office
cc: file

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Plug and Abandon	7. Unit Agreement Name
2. Name of Operator SINCLAIR OIL & GAS COMPANY	8. Farm or Lease Name Henry A. Harris
3. Address of Operator P. O. Box 1920, Hobbs, New Mexico 88240	9. Well No. 2
4. Location of Well UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 18 TOWNSHIP 12S RANGE 38E NMPM.	10. Field and Pool, or Wildcat Gladiola Devonian
15. Elevation (Show whether DF, RT, GR, etc.) 3870' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☒
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-9-68 Set C.I. plug @ 5969' w/2 sks. cement on top 5969' to 5959'. Filled hole w/mud laden material.
5-10-68 Shot off 5-1/2"OD casing @ 5008' and pulled.
5-11-68 Spotted 25 sacks cement plug in top of 5-1/2"OD casing stub 4928-5008'.
Spotted 25 sacks cement plug in bottom of 9-5/8"OD casing 4435-4500'.
5-13-68 Shot 9-5/8"OD casing off @ 629' and pulled.
5-14-68 Spotted 25 sacks cement plug in top of 9-5/8"OD casing stub @ 590-635'.
Spotted 25 sacks cement plug in bottom of 13-3/8"OD surface casing 275-325'.
Spotted 10 sacks cement plug in top of 13-3/8"OD surface casing and cellar, installed regulation plug and abandoned marker, cleaned and levelled location. Plugged and Abandoned effective 5-14-68.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John W. Runyan TITLE Superintendent

DATE 5-15-68

APPROVED BY John W. Runyan
CONDITIONS OF APPROVAL, IF ANY:

TITLE Superintendent

DATE 5-15-68