

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION
 Orig&2cc: OCC, Hobbs
 cc: Regional Office
 cc: file

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Plug and Abandon		7. Unit Agreement Name
2. Name of Operator SINCLAIR OIL & GAS COMPANY		8. Farm or Lease Name Henry A. Harris
3. Address of Operator P. O. Box 1920, Hobbs, New Mexico 88240		9. Well No. 3
4. Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM East 18' LINE, SECTION 12S TOWNSHIP 38E RANGE NMPM.		10. Field and Pool, or Wildcat Gladiola Devonian
15. Elevation (Show whether DF, RT, GR, etc.) 3870'		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-16-68 Set C.I. plug @ 11,840'. Spot 2 sks. cement on top 11,840-11,820'. Filled hole w/heavy mud laden material.

4-18-68 Shot off 5-1/2"OD casing @ 4,000' and pulled.

4-21-68 Spotted 50 sacks cement plug in 5-1/2"OD casing stub @ 4,000'. Top of plug @ 3869'.

4-22-68 Shot off 9-5/8"OD casing @ 551' and pulled. Spotted 25 sacks cement plug in 9-5/8"OD casing stub @ 551'. Top of plug @ 515'. Spot 25 sacks cement plug in bottom of 13-3/8"OD casing @ 300'. Top of plug @ 269'. Spot 10 sacks cement plug in top of 13-3/8"OD surface, set regulation dry hole marker, cleaned and levelled location. Plugged and Abandoned effective 4-22-68.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED L. M. Hembree TITLE Engineer DATE 4-23-68

APPROVED BY John W. Runyan TITLE Geologist DATE 4-27-68

CONDITION OF APPROVAL, IF ANY: