

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O.C.C.  
 NEW MEXICO OIL CONSERVATION COMMISSION  
 Orig&3cc: OCC Hobbs  
 cc: Southern Region (Texas)  
 cc: Partners  
 cc: file

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

### SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Plug and Abandon	7. Unit Agreement Name
2. Name of Operator ATLANTIC RICHFIELD COMPANY	8. Farm or Lease Name Rosa Shults
3. Address of Operator P. O. Box 1920, Hobbs, New Mexico 88240	9. Well No. 2
4. Location of Well UNIT LETTER N, 2310 FEET FROM THE West LINE AND 330 FEET FROM THE South LINE, SECTION 18 TOWNSHIP 12S RANGE 38E NMPM.	10. Field and Pool, or Wildcat Gladiola Devonian
15. Elevation (Show whether DF, RT, GR, etc.) 3873' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.  
 4-1-69 Set C.I. Plug @ 11,885' w/2 sks. cement on top 11,885-11,875'. Jet perforated 7"OD to csg. @ 9200' and 9450-51'. Set C.I. Ret. @ 9160' and squeezed perms. in 7"OD  
 4-28-69 csg. 9200' and 9450-51' w/60 sks. Incor Neat plus 3/4 of 1% CFR2 Max. Press. 3000#. Filled hole w/heavy mud laden material. Shot 7"OD csg. off @ 4560' and pulled. Spotted 85 Sacks cement plug in 7"OD csg stub @ 4560' up to 4350' in 9-5/8"OD csg. Spotted 10 sks. cement plug in top of 9-5/8"OD and 13-3/8"OD casing and cellar. Installed regulation dry hole marker and cleaned and levelled location. FMA eff 4-28-69.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED BY John W. Runyan TITLE Geologist DATE 4-28-69

CONDITIONS OF APPROVAL, IF ANY: