

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report in separate column on separate sheet.

TOOLS USED

Rotary tools were used from 0 feet to 11,955 feet, and from
Cable tools were used from 0 feet to 0 feet, and from

PRODUCTION

Put to Producing May 2, 1953

OIL WELL: The production during the first 24 hours was 3276 bbls of oil
was oil, 0 % was emulsion; 0 bbls of water, and 0 bbls of sediment
Gravity 45

GAS WELL: The production during the first 24 hours was 0 MCF of gas
liquid Hydrocarbon Shut in Pressure 0 lbs

Length of Time Shut in 0

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOLOGICAL SECTION OF STATE

Southeastern New Mexico

Northeastern New Mexico

T. Anhy.....2200	T. Devonian.....11,970	T. ...
T. Salt.....	T. Silurian.....	T. ...
B. Salt.....	T. Montoya.....	T. ...
T. Yates.....3055	T. Simpson.....	T. ...
T. 7 Rivers.....	T. McKee.....	T. ...
T. Queen.....	T. Ellenburger.....	T. ...
T. Grayburg.....	T. Gr. Wash.....	T. ...
T. San Andres.....4442	T. Granite.....	T. ...
T. Glorieta.....5880	T.	T. ...
T. Drinkard.....	T.	T. ...
T. Tubbs.....7150	T.	T. ...
T. Abo.....7842	T.	T. ...
T. Penn.....2090	T.	T. ...
T. Miss.....11,168	T.	T. ...

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
	0	13.80	Dist. from top Kelly Drive bushing to Ground		475	115	...
	34	20.20	rock		495	206	...
	180	146	Clay and Shells		5010	12	...
	380	200	red shale		5071	61	...
	1070	690	Sand and Shells		5414	343	...
	1434	364	Shells and red ed		5482	68	...
	1586	152	red Bed, Lime & Shells		5500	18	...
	1788	202	red red & Shale		5604	104	...
	2026	238	red red, lime & Shells		5700	96	...
	2217	191	red red and Anhydrite		5780	80	...
	2325	108	Anhydrite		5900	120	...
	2642	317	Salt		6000	100	...