

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, enter them in separate

TOOLS USED

Rotary tools were used from 0 feet to 12000 feet and from
Cable tools were used from feet to feet and from

PRODUCTION

Put to Producing 9-26, 19 57

OIL WELL The production during the first 24 hours was 455 bbls. of liquid
was oil 0 was emulsion, 0 was water, 0 was other liquids, A.P.
Gravity 47

GAS WELL The production during the first 24 hours was M.C.F. of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE)

Southeastern New Mexico

Southwestern New Mexico

T. Anhydrite	T. Devonian 11960'	T. Opal
T. Salt	T. Silurian	T. Kincaid
B. Salt	T. Montoya	T. Farnham
T. Yates	T. Simpson	T. Picacho
T. T. Rivers	T. McKee	T. Merit
T. Queen	T. Ellenburger	T. Port
T. Grasburg	T. Gr. Wash	T. Main
T. San Andres	T. Granite	T. Dakota
T. Glorieta 5905'		T. Mesquite
T. Drinkard		T. Pro
T. Tubbs 7160'		
T. Abco 7850'		
T. Penn		
T. Mist 11208'		

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	14		Distance from Top Kelly Drive Pushing to Ground		12000		
	2025		Red Bed				
	2198		Red Bed and Anhydrite				
	2273		Anhydrite and Gypsum				
	3029		Anhydrite and Salt				
	3606		Anhydrite				
	4047		Anhydrite and Salt				
	4235		Anhydrite and Gypsum				
	4308		Anhydrite and Lime				
	4473		Anhydrite				
	9245		Lime				
	9342		Lime and Shale				
	9371		Lime				
	9427		Lime and Shale				
	10000		Lime				

RECEIVED

FEB 03 1992

HOBBS, N. J.