

DISTRICT I  
P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-0722D

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Bronco Wolf Camp Unit

8. Well No.

6

9. Pool name or Wildcat

Bronco Wolfcamp

### SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

G.P. II Energy Corporation

3. Address of Operator

P.O. Box 50682 Midland Texas 79702

4. Well Location

Unit Letter G : 1980 Feet From The North Line and 1786 Feet From The East Line

Section 2 Township 13-South Range 38-East NMPM Lea N.M. County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3804' RKB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

#### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

#### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) 8-12-96 Set CIBP @ 9000'
- 2) 8-13-96 Circulate hole with 32 vis. 9.5# MLB
- 3) 8-13-96 Spot 25 SX cement on top of CIBP @9000' (Plug 1 9000'-8800')
- 4) 8-13-96 Cut 5-1/2" Csg @ 5088' Csg was not free
- 5) 8-14-96 Cut & lay down 5-1/2" Csg @ 4641'
- 6) 8-14-96 Spot 25 SX cement @ 5130' (Plug 2 5130'-5000')
- 7) 8-14-96 Spot 50 SX cement @ 4691' Woc & Tag next day
- 8) 8-15-96 RIH with Tbg tag TOC @ 4540' (Plug 3 4691'-4540')
- 9) 8-15-96 Cut & lay down 8-5/8 Csg @ 880'
- 10) 8-15-96 Spot 60 SX cement 930' Woc & Tag Next Day
- 11) 8-16-96 RIH with Tbg tag TOC @ 790' (Plug 4 930'-790')
- 12) 8-16-96 Spot 70 SX cement with 2% calc @ 380' Woc & Tag @ 275' (Plug 5 380'-275')
- 13) 8-16-96 Spot 35 sx cmt @ 50' (Plug #6 50'- Surf.)

Approved as to plugging of the Well Bore  
Liability under bond is retained until  
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Agent

DATE 8-16-96

TYPE OR PRINT NAME Joey Fields

TELEPHONE NO. 915-570-0829

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

GARY W. WINK

OC FIELD REPRESENTATIVE II/STAFF MANAGER