

01									

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

Operators Service Company

(Company or Operator)

Lipscomb Estate

(Lease)

Well No. 1, in NW $\frac{1}{4}$ of NW $\frac{1}{4}$, of Sec. 2, T. 13-N, R. 38-E, NMPM.Bronco (Wolfcamp)

Pool,

Lea

County.

Well is 990 feet from West line and 330 feet from North lineof Section 2. If State Land the Oil and Gas Lease No. isDrilling Commenced August 29, 19 58 Drilling was Completed September 23, 19 58Name of Drilling Contractor Sharp Drilling CompanyAddress First National Bank Bldg., Midland, TexasElevation above sea level at Top of Tubing Head 3793 GL - 3805 DF The information given is to be kept confidential until December 1, 19 58

OIL SANDS OR ZONES

No. 1, from 9055 to 9085 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8	54	New	383	None	None	None	Surface Casing
8-5/8	24 & 32	New & Used	4533	Halliburton	None	None	Salt & Oil String
5-1/2	20&15.5	New	9102	Larkin	None	9053-9114	Oil String(Liner)

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2	13-3/8	400	300	Pumps	9.5	300 barrels
11	8-5/8	4557	1300	Pumps	10.1	500 barrels
7-7/8	5-1/2	4399-9114	155	Pumps	9.8	1000 barrels

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Casing Perforations 9104-9114' - 500 gals. mud acid (Oil gas and water) Bridged off.

Casing Perforations 9053-9085' - 1000 gals mud acid - 4000 gals Reg. Acid

Casing Perforations 9053-9085' - 6000 gals. 15% NE Acid

Result of Production Stimulation

Depth Cleaned Out 9098-Top of Bridge Plug

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special test, or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 9114 feet, and from feet to feet.
Cable tools were used from 0 feet to feet, and from feet to feet.

PRODUCTION

Put to Producing November 20, 1958

OIL WELL: The production during the first 24 hours was 115.17 barrels of liquid of which 53% was
was oil; 5% was emulsion; 42% water; and 0% was sediment. A.P.I.
Gravity 44

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

T. Anhy 2264
T. Salt
B. Salt
T. Yates 3103
T. 7 Rivers
T. Queen
T. Grayburg
T. San Andres 4504
T. Glorieta 5968
T. Drinkard (Clearfork) 6617
T. Tubbs 7227
T. Abo 7914
T. Penn
T. Miss

T. Devonian
T. Silurian
T. Montoya
T. Simpson
T. McKee
T. Ellenburger
T. Gr. Wash
T. Granite
T.
T.
T.
T.
T.

Northwestern New Mexico

T. Ojo Alamo
T. Kirtland-Fruitland
T. Farmington
T. Pictured Cliffs
T. Menefee
T. Point Lookout
T. Mancos
T. Dakota
T. Morrison
T. Penn
T.
T.
T.
T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
2264	3103	839	Anhydrite				
3103	4504	1401	Yates				
4504	5968	1464	San Andres				
5968	6617	649	Glorieta				
6617	7227	610	Clearfork				
7227	7914	687	Abo				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

Bert O. Brown 12-4-58
(Date)

Company or Operator Operators Service Company

Address 201 West Bldg., Midland, Texas

Name Bert O. Brown

Position or Title Engineer