

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

December 7, 1954
(Date)Seminole, Texas
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amarada Petroleum Corporation

(Company or Operator)

L. W. Ward

(Lease)

McVay & Stafford Drilling Company, Inc.

(Contractor)

Well No. 4 in the SE 1/4 SE 1/4 of Sec. 11

T. 13-S, R. 38-E, NMPM, Undesignated - Bronco Area Pool, Lea County.

The Dates of this work were as follows: December 3rd, 4th, 5th & 6th, 1954

Notice of intention to do the work (~~SEEK~~ (was not) submitted on Form C-102 on _____, 19____, and approval of the proposed plan (~~SEEK~~ (was not) obtained.

(Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

9645 - Total Depth - Line - Finished 8-3/4" hole to 9645' at 9 p.m., 12-3-54. Ran 235 joints of 7" OD 23#, 26# & 29# Casing Now, set at 9645' with 500 sacks Slosset Cement mixed 1% Gel. Plug down to 9561' at 4 p.m., 12-3-54. Max. PP 1350#. Used Gist Centralizers & B&W Rotating Scratchers. Rotated casing until cement equalized. Ran temperature survey, found top of cement on outside of 7" OD Casing at 6532'. Ratio of actual to calculated fill- 71.4%. After waiting on cement for 31 hrs., tested 7" casing before and after drilling out cement with 1500# for 1/2 hr., held o.k.

Witnessed by C. M. Clarkson

(Name)

Amarada Petroleum Corporation

(Company)

Foreman

(Title)

Approved:

OIL CONSERVATION COMMISSION

J. G. Stanley
(Signature)
J. G. STANLEY
(Name)
ENGINEER-DIST.
(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position

Representing

Address

Dist. Supt.

Amarada Petroleum Corporation

Drawer 889 Seminole, Texas

