

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
Bronco S.W.D.	
9. Well No.	
12	
10. Field and Pool, or Wildcat	
Bronco	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER- SWD

1. Name of Operator
Amerada Hess Corporation

2. Address of Operator
Drawer D, Monument, New Mexico 88265

3. Location of Well
UNIT LETTER J, 1982.75 FEET FROM THE South LINE AND 1414.7 FEET FROM THE East LINE, SECTION 11 TOWNSHIP 13-S RANGE 38-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3810' DF

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to clean out 5-1/2" csg. w/bit & csg. scraper, shoot off 5-1/2" csg. at approx. 4580', pull & lay down same. Spot cement plug in & out of top of 5-1/2" csg. Shoot off 8-5/8" csg., pull & lay down same & spot cement plug in & out of top of 8-5/8" csg. Spot cement plug in & out of bottom of 13-3/8" csg. & spot cement plug in top of 13-3/8" csg., install marker & clean location.

THIS COPY OF THE REPORT MUST BE NOTED 24 HOURS BEFORE THE COMMENCING OF THE WORK BEING REPORTED FOR THE C-103 TO BE VALID.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E.B. Burley TITLE Supv. Adm. Ser. DATE 11-9-77

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

Expires 5/1/78

RELEASE

1977

OIL CONSERVATION COMM.
HOBBS, N. M.