

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DISTRICT OFFICE 000

MISCELLANEOUS REPORTS ON WELLS

JAN 19 1955 10:19

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

January 18, 1955

(Date)

Seminole, Texas

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amarada Petroleum Corporation

(Company or Operator)

L. W. Ward

(Lease)

McVay & Stafford Drilling Company, Inc.

(Contractor)

Well No. 5 in the NW 1/4 SE 1/4 of Sec. 11

T. 13-S, R. 38-E, NMPM, Undesignated

Pool,

Lea

County.

The Dates of this work were as follows: January 15th, 16th & 17th, 1955.

Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on _____, 19____.

(Cross out incorrect words)

and approval of the proposed plan (~~was~~) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

9660' - Total Depth - Lime - Finished 7-7/8" hole to 9660' at 12:15 a.m., 1-15-55. Ran 235 fts. 5-1/2" OD 17# Casing New, set at 9660' with 500 sacks Slosset Cement mixed 4% Gel. Plug down to 9579' at 7:00 p.m., 1-16-55. Maximum pump pressure 1300#. Rotated casing until cement equalized. Used Baker Centralizers and B&W Rotating Scratchers. Ran temperature survey, found top of cement on outside of 5-1/2" OD Casing at 7329'. Ratio of actual to calculated fill- 62.43%. After waiting on cement for 24-3/4 hours, tested 5-1/2" OD Casing with 1500# for 1/2 hr., held o.k. Drilled cement inside 5-1/2" OD Casing from 9579' to 9656'.

Witnessed by C. L. Thurman

(Name)

Amarada Petroleum Corporation

(Company)

Farm Boss

(Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

W. H. Dunlap

Position

Dist. Supt.

Representing

Amarada Petroleum Corporation

Address

Drawer 809 Seminole, Texas

(Title)

(Date)