This form is <u>not</u> to be used for reporting packer leakage tests in Northwest New Mexico

NET MEXICO OIL CONSERVATION COMMISSION

SOUTHEAST NEW MEXICO PACKER LEAKAGE TEST

Operator Sinclair Oil & Gas Co.		e Barnes & Golden		211 2. 2
Location Unit Sec	Twp 135	Rge 36E	County	Lea
Name of Reservoir or Pool	Type of Prod (Oil or Gas)	Method of Prod Flow, Art Lift	Prod. Medium (Tbg or Csg)	Choke Size
Jpper Bronce Mississippi	011	Pump	Tbg	-
Lower Compl Brenco Siluro Devenian	011	Ритр	Tbg	-
	FLOW TEST	NO. 1		
Both zones shut-in at (hour, date):	7:00 PM May 8,	1968		
Vell opened at (hour, date):	8:30 AM May 9,	1968	Uppe r Completion	Lowe r Completio
Indicate by (X) the zone producing.			х	- · · ·
Pressure at beginning of test				9
Stabilized? (Yes or No)			Yes	Yes
Maximum pressure during test				9
Ainimum pressure during test			15	9
Pressure at conclusion of test			<u>30</u>	9
Pressure change during test (Maximum	minus Minimum)			0
Mas pressure change an increase or a		Total Ti	me On	No change
Vell closed at (hour, date): 7:00 AM Dil Production During Test: 18 bbls; Grav. 43	Gas Pro	duction	on 22 1/2 Hrs. MCF: GOR -	

Rema	rks
------	-----

FLOW TEST NO. 2		-
Well opened at (hour, date): 3:30 PM May 10, 1968	Uppe r Completion	Lowe r Completion
Indicate by (X) the zone producing	·	<u> </u>
Pressure at beginning of test	85	9
Stabilized? (Yes or No)	Yes	Yes
Maximum pressure during test	89	80
Minimum pressure during test	85	9
Pressure at conclusion of test	89	40
Pressure change during test (Maximum minus Minimum)	4	71
Was pressure change an increase or a decrease?	**************************************	Increase
Oil ProductionGas ProductionDuring Test:31bbls; Grav.41.0;During Test12MCF;		
Remarks Annual test		

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

	Operator Sinclair Oil & Gas Co.
Approved 19	
New Mexico Oil Conservation Commission	By K. K. Smut
By Della	
	Title Tester - Oil Reports & Gas Services
Title	Date 5/29/68

1. A packer leakage test shall be commenced o th multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.

2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified

3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized and for a minimum of two hours thereafter, provided however, that they need not remain shut-in more than 24 hours.

4. For Flow Tes: No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued until the flowing wellhead pressure has become stabilized and for a minimum of two hours thereafter, provided however, that the flow test need not continue for more than 24 hours. 5. Following completion of Flow Test No. 1, the well shall again be shutin, in accordance Paragraph 3 above.

6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the previously shut-in zone is produced.

7. All pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked with a deadweight tester at least twice, once at the beginning and once at the end, of each flow test.

beginning and once at the end, of each flow test. 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the appropriate District Office of the New Mexico Ol Conservation Commission on Southeast New Mexico Packer Leakage Test Form Revised 11-158, together with the original pressure recording gauge charts with all the deadweight pressures which were taken indicated thereon. In lieu of filing the aforesaid charts, the operator may construct a pressure versus time curve for each zone of each test, indicating thereon all pressure changes which may be reflected by the gauge charts as well as all deadweight pressure readings which were taken. If the pressure curve is submitted, the original chart must be permanently filed in the operator's office. Form C-116 shall also accompany the Packer Leakage Test Form when the test period coincides with a gas-oil ratio test period.

