

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

November 21, 1955

(Date)

Seminole, Texas

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

(Company or Operator)

Virgil Linam

(Lease)

McVay & Stafford Drilling Company

(Contractor)

Well No. 2 in the NE 1/4 NW 1/4 of Sec. 14

T. 13-S, R. 36-E, NMPM, Bronco Siluro Devonian Pool, Lea County.

The Dates of this work were as follows: November 15th, 18th, 19th & 20th, 1955.

Notice of intention to do the work ~~(was)~~ (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)

and approval of the proposed plan ~~(was)~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

10,117' - Line - Finished 7-7/8" hole to 10,117' at 11:15 p.m., 11-15-55. Ran 267 jts. 7" OD 23#, 24# & 29# Casing New, set at 10,117' with 100 sacks Regular Cement mixed 6% Jel and 100 sacks Regular Neat Cement, total of 200 sacks. Plug down to 10,033' at 3:35 a.m., 11-19-55. Maximum pump pressure 400#. Casing was not rotated. Ran temperature survey and found top of cement on outside of 7" casing at 9678'. Ratio of actual to calculated fill- 7.34%. After waiting 28-1/2 hours for cement to set, tested 7" casing before drilling out cement with 1500# for 30 minutes, held o.k. Drilled cement inside 7" casing from 10,033' to 10,117'. Tested 7" casing after drilling out cement with 1500# for 30 minutes, held o.k. Started drilling 6" hole at 10,117' at 11 a.m., 11-20-55.

Witnessed by C. L. Thurman

(Name)

Amerada Petroleum Corporation

(Company)

Farm Boss

(Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: W. H. Quinlan

Position: Dist. Supt.

Representing: Amerada Petroleum Corporation

Address: Drawer 809 Seminole, Texas

(Title)

(Date)

