

FORMATION RECORD

<u>FROM</u>	<u>TO</u>	<u>THICKNESS IN FEET</u>	<u>FORMATION</u>
Continued			
11,783	11,802	19	Lime & Chert
11,802	12,264	462	Lime 11,940' DOD
12,264	12,351	87	Lime & Chert
12,351	12,482	131	Lime
12,482	12,490	8	Lime & Chert
12,490	12,536	46	Lime & Sand
12,536	12,537	1	Lime & Shale
12,537	12,543	6	Lime & Granite
12,543	12,548	5	Granite

E.C. Survey's

158'	1/4 Deg.	8850'	3/4 Deg.
284'	1-1/2 Deg.	8960'	1/2 Deg.
700'	1/2 Deg.	9065'	3/4 Deg.
1100'	1/2 Deg.	9180'	1/4 Deg.
1555'	3/4 Deg.	9650'	1/2 Deg.
1800'	1/2 Deg.	9900'	1 Deg.
2093'	1/4 Deg.	10030'	1-3/4 Deg.
2360'	1 Deg.	10205'	1-3/4 Deg.
2620'	1/2 Deg.	10340'	2 Deg.
2896'	1/2 Deg.	10430'	1-1/2 Deg.
3140'	3/4 Deg.	10500'	1-3/4 Deg.
3440'	3/4 Deg.	10526'	1-1/4 Deg.
3700'	1 Deg.	10557'	1-1/4 Deg.
3952'	1 Deg.	10620'	1-1/4 Deg.
4320'	1 Deg.	10710'	3/4 Deg.
4560'	1 Deg.	10740'	3/4 Deg.
4670'	3/4 Deg.	10815'	1-1/4 Deg.
4900'	1-1/4 Deg.	10923'	1-1/4 Deg.
5024'	3/4 Deg.	10980'	1-3/4 Deg.
5140'	3/4 Deg.	11070'	3/4 Deg.
5304'	3/4 Deg.	11115'	1/4 Deg.
5730'	1/2 Deg.	11150'	1/2 Deg.
5940'	3/4 Deg.	11180'	1/2 Deg.
6095'	3/4 Deg.	11230'	1/2 Deg.
6220'	3/4 Deg.	11270'	1 Deg.
6345'	1 Deg.	11305'	1 Deg.
6560'	1-1/2 Deg.	11350'	1-3/4 Deg.
6690'	1 Deg.	11550'	1-3/4 Deg.
6970'	1 Deg.	12190'	2-1/4 Deg.
7150'	3/4 Deg.	12309'	4-1/4 Deg.
7230'	3/4 Deg.	12315'	4 Deg.
7360'	1 Deg.	12334'	4 Deg.
7440'	3/4 Deg.	12390'	4-3/4 Deg.
7520'	1/2 Deg.		
7610'	1/2 Deg.		
7710'	3/4 Deg.		
7863'	3/4 Deg.		
7985'	3/4 Deg.		
8150'	1/2 Deg.		
8230'	3/4 Deg.		
8295'	3/4 Deg.		
8385'	3/4 Deg.		
8445'	1/4 Deg.		
8630'	1/2 Deg.		
8720'	3/4 Deg.		

