

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-07245

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☐ OTHER SALT WATER DISPOSAL

2. Name of Operator
MARALO, INC.

3. Address of Operator
P. O. BOX 832, MIDLAND, TX 79702

4. Well Location
Unit Letter A : 660 Feet From The NORTH Line and 660 Feet From The EAST Line

Section 20 Township 13S Range 38E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: CLEAN WELL BORE & COMPLETE AS DEVONIAN SMD ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

05/31/96 LEVEL ROAD & LOCATION. SET & TEST ANCHORS. DIG OUT CELLAR DOWN TO 13-3/8" & 9-5/8" CSG STUBS 7' BELOW G.L. ORANGE PEEL 13-3/8" CSG AGAINST 9-5/8" CSG. WELDED 2" COLLAR IN 13-3/8" CSG 8' BELOW G.L. AND PLUMBED 2" PIPE W/VALVE TO SURFACE FOR FUTURE BRADENHEAD TEST. WELD ON 9-5/8" CSG NIPPLE W/11" 3000# CSG HEAD @ SURFACE. BACK FILL CELLAR.

06/05/96 CONTINUE IN HOLE W/8-5/8" BIT #1. TAG CEMENT @ 4650' G.L. DRILL OUT CEMENT PLUG 4650' TO 4752'. LD SWIVEL. CONTINUE IN HOLE W/BIT. TAG 7-5/8" CSG STUB @ 5665' G.L. PULLED BIT UP INTO 9-5/8" CSG.

06/08/96 ATTEMPTED TO GET OVER 7-5/8" CSG. STUB.

06/13/96 UNABLE TO GET OVER 7-5/8" CSG. STUB. DECISION MADE TO TIE INTO 5-1/2" LINER INSTEAD.

06/15/96 CONTINUE IN HOLE W/6 3/4" BIT & DC'S ON DP. TAG @ 9952'. PU SWIVEL. DRILL OUT CEMENT STRINGERS TO TOP OF 5-1/2" LINER @ 10,194'. GL DP TALLEY. CIRC HOLE CLEAN. PULL BIT UP INTO 9-5/8" CSG.

06/20/96 DRESS OFF TOP OF 5-1/2" LINER IN PREPARATION OF TIE-BACK STRING.

06/25/96 RU CSG CREW. PU & TIE W/5-1/2" OD x 3' LONG 17# N80 MULE SHOE SUB W/4 - 1" CIRC HOLES 10" BELOW COLLAR + 1 JT 44.80' 5-1/2" 17# N80 LT&C CSG. + FLOAT COLLAR + 26 JTS (1159.73') 5-1/2" 17# N80 LT&C CSG + 168 JTS (7574.77') 5-1/2" 17# K55 LT&C CSG. + 32 JTS (1424.41') 5-1/2" 17# N80 LT&C CSG. STING INTO LINER HANGER TIE BACK EXTENSION @ 10,194' GL. RD CSG CREW. RU HALLIBURTON. BREAK CIRC. PUMPED 425 SXS PREM. PLUS 50/50 POZ CEMENT W/10% GEL + 3/10 CFR-3, TAIL W/200 SXS PREM CEMENT WITH 3/10 HALAD 322. RD HALLIBURTON. ND BOP. SET SLIPS CUT OFF 5-1/2" CSG. NU WELLHEAD, TEST OK.

06/26/96 RU PRO WELL TESTING & WL. RUN TEMP SURVEY. TOC @ 3600' FS.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dorothea Logan TITLE REGULATORY ANALYST DATE JUNE 27, 1996

TYPE OR PRINT NAME DOROTHEA LOGAN

TELEPHONE NO. 915 684-7441

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

JUL 5 1996

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

