



NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Fish Northwest Constructors, Inc. (Company of Operator) James W. Gray "B" (Lease)

Well No. 1, in 1/4 of 35, T. 14S, R. R33E, NMPM.

Saunders Pool, Lea County.

Well is 1980' feet from North line and 1980' feet from West line of Section 35. If State Land the Oil and Gas Lease No. is --

Drilling Commenced October 29, 1957, 19 -- Drilling was Completed January 2, 1958

Name of Drilling Contractor Clark Dale Drilling Company 308 North Colorado Patio Bldg.

Address Midland, Texas

Elevation above sea level at Top of Tubing Head 4197.7' KB The information given is to be kept confidential until --, 19 --

OIL SANDS OR ZONES

No. 1, from 9950' - 9990' to 9990' No. 4, from -- to --

No. 2, from 10,000' to 10,020' No. 5, from -- to --

No. 3, from -- to -- No. 6, from -- to --

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from -- to -- feet.

No. 2, from -- to -- feet.

No. 3, from -- to -- feet.

No. 4, from -- to -- feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	48#	New	5015x	Halliburton			
8-5/8"	32# & 24#	"	4,295'	"			
5-1/2"	17# & 15.50#	"	10,080'	"		9950-90' 10,000' 10,020'	Production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	13-3/8"	401'	365 sx	cm circ.		
	8-5/8"	4295'	2125 sx	cm circ.		
	5-1/2"	10,080'	600 sx			

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Upper perforations: 1000 gal XIST followed by 1000 gal. Reg.

Lower perforations: 500 gal XIST followed by 500 gal. Reg.

Result of Production Stimulation Production pkr set @ 9925'. After 3 runs w/swab well kicked off & flowed on a 32/64" choke, 250# pressure, until xx killed for storage. Water content estimated at less than 15%.

Depth Cleaned Out --

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from GL feet to 10,080' feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing January 2, 19 58

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T. Hueco 9264 (5068) (elec)	T. Morrison
T. Drinkard	T. XXX 9695 (-5499)	T. Penn
T. Tubbs 7106 (-2910) (elec)		
T. Abo 7818 (-3622)		
T. Penn		
T. Miss		

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1304		Red Beds	7300	8100		Sdy lime
1304	1660		Red Beds & Gyp	8100	8266		Lime & sh
1660	2180		Red Beds, Salt & Gyp	8266	8572		Sdy lime
2180	2588		Salt & Gyp	8572	8600		Lime
2588	2761		Anhy & Salt	8600	9062		Sdy lime
2761	3470		Anhy & Gyp	9062	9215		Lime
3470	3530		Anhy & Gyp & Blew Clay	9215	9308		Sdy lime & sh
3530	3710		Anhy & GYP	9308	9392		Lime & sh
3710	3870		Anhy & lime	9392	9542		Sdy lime
3870	4028		Lime & Gyp	9542	9586		Lime
4028	4158		Anhy & Gyp	9586	9626		Sdy lime
4158	4191		Lime & Gyp	9626	9652		Sdy lime & sh
4191	4249		Anhy, Gyp & lime strks	9652	9754		lime, chert & sh
4249	4292		Anhy Gyp & Lime	9754	9819		lime & sh
4292	4295		Lime & Gyp	9819	9823		lime & chert
4295	4310		Lime	9823	9876		lime, chert & sh
4310	4412		Lime & Sd	9876	9950		lime & sh
4412	4492		Sdy	9950	9993		sdly lime & sh
4492	6660		Sdy lime	9993	10,030	TD	Sh & lime
6660	6690		Lime				
6690	7230		Sdy lime				
7230	7300		Sdy lime & Sh strks				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Fish Northwest Constructors, Inc.

January 16, 1958

(Date)

Company or Operator

Address

P. O. Box 354 - Houston, Texas

Name

Manager, Oil & Gas Division