

DUPLICATE

Form C-102
(Revised 12-1-52)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

July 3, 1953
(Date)

Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation

(Company or Operator)

Lea State "CK"

(Lease)

Gardner Bros.

(Contractor)

Well No. 1 in the NW 1/4 NW 1/4 of Sec. 35

T. 14-S, R. 33-E, NMPM, Saunders Pool, Lea County

The Dates of this work were as follows: June 27-29, 1953

Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)

and approval of the proposed plan (~~was~~) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 97 Jts, 1 nipple 4218' of 9-5/8" OD 8 RT S-80 & J-55 36# SS Casing. Set & cemented at 4220' in 2 stages w/725 sacks 4% Gel & 125 sacks Neat on bottom. 2nd stage 990 sacks 4% Gel thru DV tool at 1650' & 50 sacks Neat on bottom. Plug at 4163'. 3 centralizers & 12 scratchers from 4219-4069'. Halliburton.

After waiting over 36 hrs. tested 9-5/8" casing w/1000# for 30 min, no drop in pressure. Drilled plug in Howco DV tool. Tested DV tool w/2000# for 30 min, no drop in pressure. Drilled plug from 4163' to 4220'. Tested cement below casing shoe w/800# for 30 min, no drop in pressure.

After approval of Mr. Yarbrough, State Oil and Gas Inspector, preparations were made to drill ahead.

Witnessed by J. E. Hartin
(Name)

Gulf Oil Corporation
(Company)

Drilling Foreman
(Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position Asst. Area Prod. Supt.

Representing Gulf Oil Corporation

Address Box 2167, Hobbs, New Mexico

Roy Yarbrough
(Name)
Oil & Gas Inspector
(Title)

JUL 7 1953
(Date)