NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

Н0	$BE\xi$	e Caeto	°₹ 3. c. c.
JAN	2	n . /	
•	۷	G 21	M 'Su

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

		<u> </u>	oking Below		
Notice of Intention to Change Plans		Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper		
Notice of Intention to Plug Well	x	Notice of Intention to Pluc Back	Notice of Intention to Set Liner		
Notice of Intention to Squeeze		Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)		
Notice of Intention o Gun Perforate		Notice of Intention (Other)	Notice of Intention (Other)		
OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO		Midland, Texa	s December 30	December 30, 1963	
· .•		(Place)	(Date)	
Gentlemen:					
Following is a Notic	e of Intention to do	certain work as described below at the	ne		
	(Company or Operator)	1. c Lease	Well No.	.in(Unit)	
(40-acre Subdivision)	4 of Sec	, T. 14-8 , R 35-E	Well No. 1-17 NMPM, Estacado Pennsylva	nien	
Lea	FULI (FOLLOW	nty. L DETAILS OF PROPOSED P. INSTRUCTIONS IN THE RULES 567, cement retainer at	LAN OF WORK S AND REGULATIONS)		
Condition of hole Proposed plugging Cut & proposed plugging 25 sx.] Cut & proposed plugging 25 sx.] Cut & proposed plugging 25 sx.] Line Cut &	FULI (FOLLOW) le: TD - 11, ng procedure: ull 5-1/2" caplug at 6000' plug in & out ull 8-5/8" caplug at 509' plug at surface plug at surface on to plug & a	L DETAILS OF PROPOSED P. INSTRUCTIONS IN THE RULES 567', cement retainer at sing from 8392' with 25 (Top of Glorieta). 8-5/8" casing at 4550'. sing from 2130' with 25 (Bottom of 11-3/4" casinge. ith plate.	LAN OF WORK AND REGULATIONS) 11,473'. Ex. plug in & out. Ex. plug in and out.		
Condition of hole Proposed plugging Cut & page 25 sx.] Cut & page 25 sx.] Cut & page 25 sx.] Install abandom Jerbal permission Hobbs, New Mexicon percentage permission percentage perce	FULI (FOLLOW) le: TD - 11, ng procedure: ull 5-1/2" ca plug at 6000' plug in & out ull 8-5/8" ca plug at 509' plug at surfa plug at surfa on to plug & a	L DETAILS OF PROPOSED P. INSTRUCTIONS IN THE RULES 567', cement retainer at sing from 8392' with 25 (Top of Glorieta). 8-5/8" casing at 4550'. sing from 2130' with 25 (Bottom of 11-3/4" casing ce. ith plate. abandon obtained Decembe	LAN OF WORK AND REGULATIONS) 11,473'. Ex. plug in & out. Ex. plug in and out. g). 127, 1963, from Mr. Eric	c Engbre cht,	
Condition of hole Proposed plugging Cut & programme 25 sx.] Cut & programme 25 sx.] Cut & programme 25 sx.] Install abandom Verbal permission	FULI (FOLLOW) le: TD - 11, ng procedure: ull 5-1/2" ca plug at 6000' plug in & out ull 8-5/8" ca plug at 509' plug at surfa plug at surfa on to plug & a	L DETAILS OF PROPOSED P. INSTRUCTIONS IN THE RULES 567', cement retainer at sing from 8392' with 25 (Top of Glorieta). 8-5/8" casing at 4550'. sing from 2130' with 25 (Bottom of 11-3/4" casing ce. ith plate. abandon obtained Decembe	LAN OF WORK AND REGULATIONS) 11,473'. Ex. plug in & out. Ex. plug in and out. g). 127, 1963, from Mr. Eric Company of California	c Engbre cht,	
Condition of hole Proposed plugging Cut & page 25 sx.] Cut & page 25 sx.] Cut & page 25 sx.] Install abandom Jerbal permission Hobbs, New Mexicon percentage permission percentage perce	FULI (FOLLOW) le: TD - 11, ng procedure: ull 5-1/2" ca plug at 6000' plug in & out ull 8-5/8" ca plug at 509' plug at surfa pent marker w on to plug & a	L DETAILS OF PROPOSED P. INSTRUCTIONS IN THE RULES 567', cement retainer at sing from 8392' with 25 (Top of Glorieta). 8-5/8" casing at 4550'. sing from 2130' with 25 (Bottom of 11-3/4" casing ce. ith plate. abandon obtained Decembe	LAN OF WORK AND REGULATIONS) 11,473'. Ex. plug in & out. Ex. plug in and out. g). 127, 1963, from Mr. Eric Company of California Company or Operator	c Engbrecht	
Condition of hole Proposed pluggin Cut & pa 25 sx.] Cut & pa 25 sx.] Cut & pa 25 sx.] Install abandom Perhal permission Hobbs, New Mexical Proposed State of the part of th	FULI (FOLLOW) le: TD - 11, ng procedure: ull 5-1/2" ca plug at 6000' plug in & out ull 8-5/8" ca plug at 509' plug at surfa pent marker w on to plug & a	L DETAILS OF PROPOSED P. INSTRUCTIONS IN THE RULES 567', cement retainer at sing from 8392' with 25 (Top of Glorieta). 8-5/8" casing at 4550'. sing from 2130' with 25 (Bottom of 11-3/4" casing ce. ith plate. abanden obtained December By	LAN OF WORK AND REGULATIONS) 11,473'. Ex. plug in & out. Ex. plug in and out. g). r 27, 1963, from Mr. Eric Company of California Company or Operator Production Clerk	c Engbrecht	