NUMBER OF COPI			
D1	STRIBUTI	0 N	
SANTA FI			_
FILE		1	1
U. S. G. S.		t	
LAND OFFICE			
TRANSPORTER	OIL	1	_
	GAS		1
PRORATION OFFIC	C.E.		
OPERATOR			

NEW MEXICO OIL CONSERVATION COMMISSION BBS OFFICE 0. C. C.

Aug 4 10 23 AM '64 MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL	Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well	x	Notice of Intention to Plug Back	Notice of Intention to Set Liner	
Notice of Intention to Squeeze		Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate		Notice of Intention (Other)	Notice of Intention (Other)	

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Hobbs,	New.	Mancico	
•	(Place)		

July 31, 1964

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation	Northwest Tatum	n State Unit		.inJ
(Company or		Lunse		(Unit)
NW. 1/4	10 T 12S	R. 358 NMPM	Mildcat	Pool
(40-acre Subdivision)	• • •	,	•	

Lea. County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 11,500*. It is proposed to plug and abandon as follows:

11,400-11,500, 30 sacks, across Top Strawn and bottom hole plug. 10,600-10,700, 60 sacks, across Top Penn , 35 sacks, across Wolfcamp 9500-9600* 60 sacks, across Abo 7950-80501 . 1, 35 sacks, isolate Gleristta equivalent porosity 6600-6700* , 35 sacks, isolate San Andres porosity 5500-5600* , 35 sacks, across 9-5/8" casing 4250-4350* , 25 sacks, surface. 0-501

If casing cut above 2300* a 100* plug will be set across stub of 9-5/8* and 100* across surface casing shoe. If casing is cut below 2300*, additional plug will be required to isolate the salt in addition to above plugs.

Verbal permission to plug and abandon received from Mr. Engbrecht 7-30-64 to J. D. Mussett.

Approved	Gulf Oil Corporation
Except as follows:	Company of Operator ORIGINAL SIGNED BY
	By
_	Position Area Production Manager
Approved	Position
OIL CONSERVATION COMPILISSION	
By for an and	Name Gulf Oil Cerporation
Title	Address
	Concernment of A.S. state A.S. state