

| NUMBER OF COPIES RECEIVED | |
|---------------------------|------------|
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| TRANSPORTER | OIL GAS |
| PRORATION OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

| | | | | | |
|--------------------------------------|-----------|---|--|--------------------------------------|--|
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL | | NOTICE OF INTENTION TO DRILL DEEPER | |
| NOTICE OF INTENTION TO PLUG WELL | XX | NOTICE OF INTENTION TO PLUG BACK | | NOTICE OF INTENTION TO SET LINER | |
| NOTICE OF INTENTION TO SQUEEZE | | NOTICE OF INTENTION TO ACIDIZE | | NOTICE OF INTENTION TO SHOOT (Nitro) | |
| NOTICE OF INTENTION TO GUN PERFORATE | | NOTICE OF INTENTION (OTHER) | | NOTICE OF INTENTION (OTHER) | |

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

January 19, 1965

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Skelly Oil Company

Hobbs "P"

1

"K"

Well No. in (Unit)

NE

SW

(Company or Operator)

14-5

34-1/2

E. Saunders Permo Perm.

Pool

1/4 of Sec., T., R., NMPM.,

(40-acre Subdivision)

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well is no longer economical to operate. There are no other commercial zones of oil or gas in this well. We plan to plug and abandon the well in the following manner:

1. Move in and rig up pulling unit.
2. Spot 25 sack cement plug over 5-1/2" OD casing perfs. 10,421-10,429'.
3. Rig down and move out pulling unit.
4. Move in and rig up hydraulic casing jacks.
5. Run free point indicator on 5-1/2" OD casing.
6. Cut and pull 5-1/2" OD casing from approx. 8200'.
7. Spot 25 sack cement plug in and out of cut off point on 5-1/2" OD casing.
8. Spot cement plugs as follows:

25 sacks - At top of Tubb 7300'

25 sacks - At top of Clearfork 6700'

25 sacks - At top of Glorieta 5900'.

(Continued on reverse side)

Approved....., 19.....
Except as follows:Approved.....
OIL CONSERVATION COMMISSION

By.....

Title.....

Skelly Oil Company

(ORIGINAL COPY OPERATED
SIGNED) H. E. Ass

By.....

Dist. Superintendent

Position.....

Send Communications regarding well to:

Skelly Oil Company

Name.....

Box 730 - Hobbs, New Mexico

Address.....

9. Spot 25 sack cement plug in and out of 8-5/8" OD casing point at 4491'.
10. Run free point indicator on 8-5/8" OD casing.
11. Cut and pull 8-5/8" OD casing from approx. 2450'.
12. Spot 25 sack cement plug in and out of cut off point on 8-5/8" OD casing.
13. Spot 25 sack cement plug at top of the Anhydrite 1843'.
14. Spot 25 sack cement plug in and out of 13-3/8" OD casing point at 3001'.
15. 10 sack plug at surface in top of 13-3/8" OD casing with 4" steel marker.
16. All intervals not cemented will be filled with heavy mud laden fluid.