

## NEW MEXICO OIL CONSERVATION COMMISSION

**Santa Fe, New Mexico**

**WELL RECORD**

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in **QUINTUPLICATE**. If State Land submit 6 Copies

AREA 640 ACRES  
LOCATE WELL CORRECTLY

TEXACO Inc.

H. H. Harris

.....  
(Company or Operator)

(Lease)

Well No. 2, in SW  $\frac{1}{4}$  of SE  $\frac{1}{4}$ , of Sec. 35, T. 12-S, R. 38-E, NMPM.

Bronco Wolfcamp & Bronco Siluro Devonian Pool. Lea County.

Well is 650 feet from South line and 1800 feet from East line

of Section.....35..... If State Land the Oil and Gas Lease No. is.....Patented.....

Drilling Commenced August 17 1964 Drilling was Completed October 8 1964

Name of Drilling Contractor.....Cactus Drilling Company.....

Address..... P. O. Box 32 - Midland, Texas

Elevation above sea level at Top of Tubing Head.....3800' (D. F.)..... The information given is to be kept confidential until  
January 19 65

See the attached sheet.

### OIL SANDS OR ZONES

No. 1, from.....to..... No. 4, from.....to.....

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

Drilled with rotary tools and no water sands tested.

## IMPORTANT WATER SANDS

**Include data on rate of water inflow and elevation to which water rose in hole.**

No. 1, from..... to..... feet.

No. 2, from ..... to ..... feet. ....

No. 3, from.....to.....feet.

No. 4, from.....to.....feet.

### CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13 3/8"	23.72	NEW	504'	Howco	NONE	NONE	Surface
8 5/8"	24.00	NEW	4618'	Howco	NONE	NONE	Intermediate
3 1/2"	9.20	NEW	11839'	Howco	NONE	See attached	Production
2 7/8"	6.50	NEW	11833'	Howco	NONE	See attached	Production

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2"	13 3/8"	519'	500			
10 3/4"	8 5/8"	4630'	600			
7 7/8"	3 1/2"	11847'	1200			
7 7/8"	2 7/8"	11846'	1200			

### RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Ots. or Gals. used, interval treated or shot.)

See the attached sheet.

**Result of Production Stimulation** See the attached sheet.

...Depth Cleaned Out....11.850!

# RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

## TOOLS USED

Rotary tools were used from 0 feet to 11,850 feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

## PRODUCTION

Put to Producing October 23, 1964

OIL WELL: The production during the first 24 hours was 212 barrels of liquid of which 98 % was  
was oil; % was emulsion; 2 % water; and % was sediment. A.P.I.  
Gravity 48

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of  
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

### Southeastern New Mexico

T. Anhy 2240'  
T. Salt 2340'  
B. Salt 3060'  
T. Yates 3087'  
T. 7 Rivers  
T. Queen  
T. Grayburg  
T. San Andres 4473'  
T. Glorieta 5940'  
T. Drinkard  
T. Tubbs 7180'  
T. Abo 7853'  
T. Wolfcamp 9238'  
T. Cisco 9712'

### Northwestern New Mexico

T. Devonian Strawn 10430'  
T. Silurian Atoka 10788'  
T. Lower Miss. 11097'  
T. Simpson Woodford 11733'  
T. McKee Devonian 11784'  
T. Ellenburger  
T. Gr. Wash  
T. Granite  
T.  
T.  
T.  
T.  
T.  
T.  
T.

T. Ojo Alamo  
T. Kirtland-Fruitland  
T. Farmington  
T. Pictured Cliffs  
T. Menefee  
T. Point Lookout  
T. Mancos  
T. Dakota  
T. Morrison  
T. Penn  
T.  
T.  
T.  
T.

## FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	258	258	Caliche				
258	1130	872	Redbed				
1130	2240	1110	Redbed & Sand				
2240	2340	100	Redbed & Anhy				
2340	3060	720	Anhy & Salt				
3060	4400	1340	Anhy & Lime				
4400	5610	1210	Lime				
5610	6890	1280	Lime & Sand				
6890	8165	1275	Lime				
8165	9540	1375	Lime & Shale				
9540	10111	571	Lime & Sand				
10111	10870	759	Lime, Shale & Chert				
10870	11238	368	Lime & Chert				
11238	11850	612	Lime & Shale				
Total Depth	11850						
All measurements from rotary table or 12' above ground level.							
Estimate Number	8172						
5 - NMOCC - Hobbs, New Mexico							
1- Field							
1- File							

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator TEXACO Inc.  
Name H. D. Raymond  
Address P. O. Box 728 - Hobbs, New Mexico  
Position or Title Assistant District Superintendent  
Date October 28, 1964