

LEA
TEXACO INC.

Saunders

N.M.

Sec. 22-14S-33E
#9 State of New Mexico "AN" Page #2

8-24-64 TD 10,000', PBD 9998', prep to Ac.
Ac. 1000 gals. 9882-9888'.
Swbd. 40 BLO + 31 BNO + 24 BAW & 38 BFW/14 hrs.
Swbd. 40 BFW/14 hrs.
Sq. Perfs. 9882-88' w/50 sx.
Re-Perf. 9880-85' w/2 SPF.
8-31-64 TD 10,000', PB 9998', swbg.
Ac. 500 gals. 9880-85'.
Swbd. 40 BLO + 2 BNO + 12 BAW + 21 BNW/6 hrs.
Swbd. 18 BO + 22 BFW/12 hrs.
Perf. @ 9766', 9776', 9783', 9792', w/2 SPI.
Set Ret. BP @ 9845'.
Swbd. 4 BO + 120 BW/23 hrs.
9-8-64 TD 10,000', PB 9998', swbg.
Ac. 500 gals. 9766-92'.

9-14-64 Swbd. 37 BLO + 12 BAW + 9 BFW/7 hrs.
Swbd. 13 BNO + 51 BLW + 66 BFW/36 hrs.
TD 10,000' PB 9998', swbg.
Re-Ac. 2000 gals. 9766-92'.
Swbd. 10 BNO + 205 BFW/24 hrs.
Vis-Sq. Perfs 9766-92' w/75 sx.
9-21-64 TD 10,000', PB 9998', swbg.
Swbd. perfs. 9766-92' & swbd. dry.
Perf. @ 9862', 9863', 9864', 9882', 9883',
9884', 9885' w/1 SPI.
Ac. 500 gals.
Swbd. 39 BLO + 12 BLW + 1 BNW/16 hrs.
9-28-64 TD 10,000', PB 9998', swbg.
Re-Ac. 1000 gals. 9862-85'.
Swbd. 2 BNO + 22 BNW/24 hrs.
10-5-64 TD 10,000', PB 9998', swbg.

COUNTY	LEA	FIELD Saunders	STATE NM	OWWO
OPR	TEXACO INC.			
	9 New Mexico "AN" State		MAP	
	Sec. 22, T-14-S, R-33-E		30-225-20955	
	660' FNL, 1980' FWL of Sec.		CO-ORD	
Re-Cmp 5-31-68	CLASS	OWDF	EL	
CSG & SX - TUBING	FORMATION	DATUM	FORMATION	DATUM
10 3/4" 388' 400				
7 5/8" 4120' 850				
4 1/2" lnr 4003-9999' 700				
LOGS EL GR RA IND HC A				
	TD 10,000'	PBD 9998'		
Pennsylvanian Perfs 9808-9885' - NO NEW POTENTIAL				

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 9900' TYPE WO

6-17-68 F.R.C. 6-20-68; OWWO
PD 9900' - Penn.
(Orig. Cmp 11-2-64 thru Perfs 9862-85', OTD 10,000', OPB 9998')
Elev. 4223' DF, Orig.
TD 10,000', PBD 9998', COMPLETE
Perf 9808-10', 9822-26', 9830-32' W/2 SPF
Acid (9808-32') 2000 gals (15%)

10-5-64 - cont. -

Set Pkrs @ 9827' & 9734'
Re-Ac. 2500 gals 9766-9792'
Swbd 213 BFW/24 hrs.

10-12-64 TD 10,000', PBD 9998', SI.

10-19-64 TD 10,000', PBD 9998', SI.

10-26-64 TD 10,000', PBD 9998', prep to drill out.
Set CIBP @ 9820'

Squeezed perfs 9766-92' W/75 sx.

Squeezed 4½" liner w/100 sx.

11-2-64 TD 10,000', PBD 9998', COMPLETED
DO to 9958'

Re-Ac. 1000 gals 9862-85'.