

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Delaware Apache Corporation	5. State Oil & Gas Lease No. OG 5909
3. Address of Operator 2000 Wilco Building, Midland, Texas	7. Unit Agreement Name High Plains Unit
4. Location of Well UNIT LETTER 0 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 15 TOWNSHIP 14S RANGE 34E RANGE	8. Farm or Lease Name High Plains Unit
	9. Well No. 2
	10. Field and Pool, or Wildcat High Plains Penn. Trt.
15. Elevation (Show whether DF, RT, GR, etc.) 4111 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

A. W. Thompson Drilling Co. spudded 1: A.M. 3/8/65.
Drilled 15" hole to 362'. Ran 12 jts 11 3/4" O.D. 42 #/ft H-40 ST&C casing.
Howco cemented with 200 sxs Class "C" + 4% Gel + 2% NaCl and 175 sxs Class "C" + 2% CaCl₂.
Cement circulated to surface. WOC 18 hours.
Tested cement job, casing, and blow-out-preventor with 900 psi for 30 mins. Held OK.

Drilled 11" hole to 4530'.
Ran 142 jts 8 5/8" casing as follows:
73 jts 8 5/8" 32# J-55 ST&C - 2379.11', and
69 jts 8 5/8" 24# J-55 ST&C - 2158.22'.
Set @ 4530'. Internal float @ 4466'.
Howco cemented w/ 200 sxs Class "C" + 4% Gel + 2% NaCl and 150 sxs Class "C" + 2% CaCl₂.
WOC 18 hours. Tested casing, cement job, and BOP w/ 1000 psi for 30 mins. Held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE **District Engineer** DATE **March 17, 1965**

APPROVED BY [Signature] TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: