

J. M. HUBER CORPORATION DAILY WELL REPORT

District Midland

Well Pure-State #1 County Lea County, New Mexico ^{Oct 15 11 01 AM '55}
 Location 660 FW & 1980 FN Line of Sec. 16, T-14-S, R-34-E.
 Operator J. M. Huber Corp. Contractor Hondo Drilling Co. Huber WI 100%
 Remarks

Date	Depth	Report
8-23-65		Spudded 8 P.M. Drilled 17-1/4" hole to 400'. T.D. @ 400'. Kellybushing 11' above ground level. Dev. 1/4" @ 350'. Ran 375' of 13-3/8" 48# H-40 csg and 25' of 13-3/8" 54# J-55, Set with 180 sacks Class "C", 8% gel, 150 sacks Class "C" Neat. Circulated 50 sacks to pit.
8-24-65		Plug down 7:30 A.M. New Mexico Time. W.O.C.
8-25-65		Drilling @ 1300' in Redbed. Bit No. 1, Dev. 1/2° @ 845'. Tested 13-3/8" Casing to 500#, held O.K.
8-26-65		Drilling @ 2580' in Anhydrite and salt. Dev. 1/2° @ 1300', 3/4° @ 1800', 1/2° @ 1914, 1/2° @ 2400'
8-27-65		Drilling at 3030' in anhydrite and lime. Bit No. 3, Dev. 3/4° @ 2750, 1/2° @ 3030'.
8-28-65		drilling @ 3481' in anhydrite and salt. Bit No. 3, Mud Wt. 10, Vis. 33.
8-29-65		Drilling @ 3856 in anhydrite and lime. Bit No. 4, Dev. 1° @ 3465, 1° @ 3740, Mud Wt. 10.7, Vis. 33.
8-30-65		Drilling @ 4155' in lime. Bit No. 5, Mud wt. 10.7, Vis. 34, Dev. 3/4° @ 4071.
8-31-65		T.D. @ 4405' in Lime. Mud Wt. 10.7, Vis. 34, Dev. 1/2° @ 4369'. Preparing to run 8-5/8" csg.
9-1-65		Ran 8-5/8" 24 & 32 # J-55 Casing to 4405'. Cemented with 200 sacks incore class "C" 1% Calcium Chloride. Plug down @ 6:15 P.M. 8-31. W.O.C. 12 hrs.
9- 2-65		Drilling @ 4749' in Dolomite. Bit No. 7, Dev. 1/2° @ 4749'.
9-3-65		Drilling @ 5093 in Dolomite, Bit No. 9, Dev. 1/2° @ 5038'.