

COUNTY	LEA	FIELD	Saunders, East	STATE	NM
OPR	HUBER, J. M.				MAP
1 Pure-State					
Sec. 16, T-14-S, R-34-E					CO-ORD
1980' fr N Line & 660' fr W Line of Sec.					
Spd 8-23-65		CLASS		E	
Cmp 10-8-65		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
13 3/8"	400'	330			
8 5/8"	4405'	230			
4 1/2"	10657'	240			
LOGS EL GR RA IND HC A					
		TD 10657'			

IP Permian-Pennsylvanian Perfs 10347-502' Flwd 374 BOPD. Pot.
Based on 24 hr test thru 24/64" chk., TP 300#, CP Pkr, Gravity
46., GOR 435.

Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.	
CONT. Hondo Drlg. Co.	PROP DEPTH 10,700' TYPE
DATE	

F.R. 8-19-65; Oper's Elev. 4147' DF
PD 10,700' - Wolfcamp
Contractor - Hondo Drlg. Co.
8-30-65 Drlg. 4155' lm.
9-7-65 Drlg. 6631' dolo.
9-13-65 Drlg. 8634' dolo.
9-20-65 TD 9880' dolo., on DST 9650-9880'.
9-28-65 Drlg. 10535'.
DST 9650-9880', open 30 mins,
Rec 10' drlg fluid
1 hr 40 min ISIP 858#, FP 111-111#,
1 hr FSIP 188#.
DST 10310-390', open 3 hrs,
GTS 18 mins @ 55 MCFGPD to 88 MCFGPD thru
1/4" chk.
Rec 1456' free oil + 50' DM,
1 hr ISIP 3891#, FP 102-511#,
2 hr 35 min FSIP 3725#.

9-28-65 Continued
DST 10390-500', open 1 hr,
GTS 3 mins @ TSTM,
rec 9885' free oil + 60' O&GCM,
1 hr ISIP 2381#, FP 588-1818#,
1 hr FSIP 2381#.
10-4-65 TD 10657', prep to perf.
Perf 10486-489', 10495-502' W/2 SPF
Ac. 500 gals (MA)
10-11-65 TD 10657', WO Potential.
Perf 10442-448' W/2 SPF
Ac. 500 gals.
Swbd load.
Perf 10347-430' W/2 SPF
Ac. 3000 gals (10347-448')

Swbd & Flwd 9 BFPH (40% wtr) for 12 hrs
10347-448'.
10-18-65 TD 10657', COMPLETED.
LOG TOPS: Anhydrite 1840', San Andres 4330',
Yeso 5876', Tubb 7298', Abo 8034', Wolfcamp
Lime 9563', Pennsylvanian 10346'.