

RICT I  
Box 1980, Hobbs, NM 88240

RICT II  
O. Drawer DD, Artesia, NM 88210

RICT III  
000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-21287
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. K-1038
7. Lease Name or Unit Agreement Name  State "C"
8. Well No. 1
9. Pool name or Wildcat Nonombre Upper Penn

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☐ OTHER P&A

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line

Section 32 Township 13S Range 34E NMPM Lea County  
10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3168' KB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to plug and abandon well as follows:

Set CIBP at 10600' and cap w/35' cement.

Set CIBP at 10250' and cap w/35' cement.

Spot 35 sx cement plug from 8000-7900'.

Spot 35 sx cement plug from 6200-6100'.

Perforate 4 squeeze holes @ 4350', set retainer @ 4250' and squeeze w/75 sacks.

Perforate 4 squeeze holes @ 1849', set retainer @ 1800' and squeeze w/75 sacks.

Note: Leave 35' cement on top of each retainer.

Perforate 4 squeeze holes @ 375'. Pump cement down 5½" casing and circulate cement out 8-5/8" x 5½" annulus. Leave 100' cement inside casing above perfs.

Spot 10 sx at surface and install abandonment marker.

NOTE: Notify NMOCD, Hobbs, NM, before starting operations. (505) 393-6161

Load hole w/25#/bbl salt gel mud between plugs.

Verbal approval obtained from Paul Kautz, NMOCD, Hobbs, 4-21-93, by Ray Stall, Yates Petroleum.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-26-93  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

Orig. Signed by  
**Paul Kautz**  
Geologist

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE APR 28 1993

CONDITIONS OF APPROVAL, IF ANY:

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PRODUCTION OPERATIONS FOR THE WELL

DP